



LEGEND	
SYMBOL	DESCRIPTION
(E)	EXISTING
(N)	NEW
[Line]	EXISTING WALL
[Line]	(N) BEARING PARTITION WALL
[Line]	(N) NON-BEARING PARTITION WALL
[Line]	(N) NON-BEARING PARTITION WALL
[Line]	(N) PREFABRICATED WALK-IN COOLER WALL UNDER SEPARATE SUBMITTAL BY REFRIGERATION CONSULTANT
[Line]	LOCATION OF MILLWORK
[Line]	LOCATION OF NOT T.I. PROJECT AREA
[Symbol]	REFERENCE TO WALL PARTITION. PARTITION TYPES & DETAIL SEE A6.0
[Symbol]	REFERENCE TO NUMBERED NOTES FOR THIS SHEET.
[Symbol]	REFERENCE TO DOOR NUMBERS. REFER TO DOOR SCHEDULE (E: EXISTING DOOR TO REMAIN)
[Symbol]	REFERENCE TO WINDOW NUMBERS. REFER TO WINDOW SCHEDULE (E: EXISTING WINDOW TO REMAIN)
[Symbol]	REFERENCE TO EQUIPMENT NUMBERS. REFER TO KITCHEN EQUIPMENT SCHEDULE

GENERAL NOTES FOR THIS SHEET:

- SEE ENLARGED PLANS SHEET AXXXX AND AXXXX FOR NEW DINING AREA SEAFOOD DISPLAY AREA AND RESTROOM.
- CASEWORK BY H-MART, COORDINATE WITH H-MART PROJECT MANAGER.
- UNLESS NOTED OTHERWISE ALL FIXTURES AND EQUIPMENT ARE TO BE FURNISHED BY H-MART AND INSTALLED BY G.C.
- SEPARATE PERMIT IS REQUIRED FOR ALL FIXTURE ANCHORAGE.
- REFER TO REFRIGERATION DWGS FOR ADDITIONAL INFORMATION.
- PROVIDE FIRE SPRINKLERS IN ALL VOID SPACES PROVIDE TWO 24" SQUARE ACCESS DOOR TO ALL VOID SPACES COORDINATE LOCATION OF ACCESS DOORS WITH H-MART PROJECT MANAGER.
- FLOOR SINKS THAT ARE SERVING LOW SETTING EQUIPMENT SHALL BE HALF EXPOSED.
- PRIME AND PAINT WASTE AND CONDENSATE.
- H-MART TO PROVIDE AND INSTALL CASE BUMPER GUARD G.C. TO COORDINATE WITH H MART.
- ALL DIMENSIONS TO FACE OF STUD OR SMU(UNO)
- REFER TO INTERIOR DECOR DWGS, FOR FLOOR AND WALL FINISHES.
- REFER TO ENLARGED FIXTURE PLAN ON SHEET A7.K1 FOR EQUIPMENT SCHEDULE AND NOTED.
- WHERE FIXED OR BUILT-IN TABLES AND COUNTERS OR SEATS ARE PROVIDE FOR THE PUBLIC AND IN GENERAL EMPLOYEE AREA 5%(BUT NEVER LESS THAN ONE) MUST BE ACCESSIBLE PER SECTION 112B.1
- THE TOP OF TABLES AND COUNTERS SHALL BE 28" TO 34" FROM THE FLOOR WHERE A SINGLE COUNTER CONTAINS MORE THAN ONE TRANSACTION STATION SUCH AS A BANK COUNTER WITH MULTIPLE TELLER WINDOWS OR A RETAIL SALES COUNTER WITH MULTIPLE CASH REGISTER STATION AT LEAST 5%(BUT NEVER LESS THAN ONE OF EACH TYPE OF STATION) SHALL BE LOCATED AT A SECTION OF COUNTER THAT IS AT LEAST 36" LONG AND NO MORE THAN 28" TO 34" HIGH PER SECTION 112B.4
- SHOW OR NOTED THAT THE PROPOSED GENERAL SALES,DISPLAY AND OFFICE AREA ARE ACCESSBLE PER SECTION 110B.1 AS FOLLOWING
 - WORK STATIONS ARE LOCATED ON ACCESSIBLE LEVELS
 - THE CUSTOMER SIDE OF SALES OR CHECKOUT STATIONS ARE ACCESSIBLE
 - EMPLOYEE WORK AREAS ARE FIXED AND ARRANGED TO PROVIDE ACCESS TO EMPLOYEES IN WHEELCHAIRS
 - CHECKSTANDS SHALL PROVIDE
 - A 36" ASLE ON THE CUSTOMER SIDE OF THE CHECKSTAND
 - WHERE QUICK CHECKSTANDS ARE PROVIDED MORE THAN OR EQUAL TO 1 SHALL BE ACCESSBLE
 - WHERE REGULAR CHECKSTANDS ARE PROVIDED MORE THAN OR ACCESSBLE CHECKSTANDS SHALL BE AS FOLLOWS PER TABLE 111B.2
 - MORE THAN OR EQUAL TO 1 BUT LESS THAN OR EQUAL TO 4 REGULAR
 - MORE THAN OR EQUAL TO 5 BUT LESS THAN OR EQUAL TO 8 REGULAR TOTAL= 2 ACCESSBLE
 - MORE THAN OR EQUAL TO 9 BUT LESS THAT OR EQUAL TO 15 REGULAR TOTAL= 3 ACCESSBLE
 - MORE THAN OR EQUAL TO 15 REGULAR TOTAL -3 +AND ADDITIONAL 20% ACCESSBLE
 - ACCESSBLE CHECKSTANDS SHALL PROVIDE A CLEAR CHECK-OUT ASLE WIDTH OF 36" WITH AN ADJOINING COUNTER LESS THAN OR EQUAL TO 38" ABOVE FINISHED FLOOR NOTE THAT THEY WILL ALWAYS OPEN AND BE IDENTIFIED BY SIGN CLEARLY VISBLE TO THOSE IN WHEELCHIRS
 - UNREINFORCED CONCRETE SLABS MAY NOT BE USED TO RESIST SESMIC UPLIFT LOADS (HOWEVER, A MAXIMUM UPLIFT OF 1000# IS ALLOWED ON 5"+ THICK SLABS WITHOUT STEEL REINFORCEMENT) COMPLETE DESIGN FOR ANY RACKS OVER 8' HIGH TO BE PROVIDE
 - ALL STORAGE RACKS AND SHEL VINGS ARE 5'-9"MAX HT FROM FINISHED FLOOR.
 - ALL STAINLESS STEEL CORNER BEAD AND GUARDRAIL PROVIDE BY H-MART INSTALL BY GC.
 - AN PROVIDED SMISMIC GAS SHUTOFF VALE WILL BE INSTALLED ON THE FUEL GAS LINE ON THE DOWN STREAM SIDE OF THE UTILITY METER AND RIDGIDLY CONNECTED TO THE EXTERIOR OF THE BUILDING OR STRUCTURE CONTAINING THE FUEL GAS PIPING * (PER ORDINANCE 170,158) (INCLUDES COMMERCIAL ADDITIONS AND TI WORK OVER \$10,000.) SEPARATE PLUMBING PERMIT IS REQUIRED.
 - FLOOR FINISHES SHALL BE SLIP RESISTANT

(E) MEZZANINE FLOOR PLAN 02
Scale: 3/32" = 1'-0"

FLOOR PLAN 01
Scale: 3/32" = 1'-0"

CORBeL
architects

WWW.CORBELARCHITECTS.COM

3450 Wilshire Blvd Suite 1000
Los Angeles, California 90010
T: 1 213 739-9902
F: 1 213 739-9906

Project:

H MART
Torrance,LLC

@VISTA PLAZA SHOPPING CENTER
4340 Pacific Coast Highway,
Torrance, California 90505

Project Owner:



300 Chubb Ave
Lyndhurst, NJ 07071

T: 1 201 507 9900
F: 1 201 507 9600

Engineer:

Architect / Engineer Seal:

THE DRAWINGS AND SPECIFICATIONS, SEALS, RECORDS AND ARRANGEMENTS ARE AND SHALL REMAIN THE PROPERTY OF THE ARCHITECT AND PART THEREOF SHALL BE COPIED OR USED IN CONNECTION WITH ANY WORK OR PROJECT OTHER THAN THE SPECIFIC PROJECT FOR WHICH THEY HAVE BEEN PREPARED WITHOUT THE WRITTEN CONSENT OF THE ARCHITECT.

NO	ISSUED	DATE
1	DESIGN REVIEW	8/28/2014
2	DESIGN REVISE	10/8/2014
3	DESIGN REVISE	12/9/2014
4	CUP PERMIT	12/15/2014
5	HEALTH PERMIT	5/1/2015

Project No:

14012

Drawn By:

Checked By:

Sheet Name:

OVERALL FLOOR PLAN

Sheet No:

A2.01

CUP PERMIT SET