



CONCEPTUAL FLOOR PLAN

3/32" = 1'-0"

FLOOR PLAN KEYNOTES

- 1 FIRE RISER / FIRE DEPARTMENT CONNECTION
- 2 KNOX BOX PER CITY OF MESA REQUIREMENTS AT 5'-0" A.F.F.
- 3 CMU WALL
- 4 STUCCO OVER FOAM OVER CMU WALL
- 5 STUCCO OVER FOAM OVER WOOD SHEATHING OVER METAL STUD FRAMING WALL
- 6 ALUMINUM COMPOSITE MATERIAL OVER SHEATHING OVER CMU WALL
- 7 ALUMINUM COMPOSITE MATERIAL OVER SHEATHING OVER METAL STUD FRAMING WALL
- 8 ROOF ACCESS LADDER AND ROOF HATCH
- 9 STRUCTURAL COLUMN- SEE STRUCTURAL DRAWINGS
- 10 ROOF DRAIN AND OVERFLOW DRAIN LEADERS DAYLIGHT WITH LAMBS TONGUE SPOUTS- SEE PLUMBING DRAWINGS
- 11 DASHED LINE INDICATES LINE OF CANOPY ABOVE
- 12 ALUMINUM FRAME WINDOW SYSTEM WITH 1" OFFSET INSULATED GLAZING
- 13 HOSE BIBB- SEE PLUMBING DRAWINGS
- 14 14'-0"x14'-0" OVERHEAD COILING DOOR- INSTALL 3"x3"x4'-0" STEEL CORNER GUARDS AT ALL OVERHEAD DOOR LOCATIONS
- 15 12'-0" X 12'-0" OVERHEAD COILING DOOR- INSTALL 3"x3"x4'-0" STEEL CORNER GUARDS AT ALL OVERHEAD DOOR LOCATIONS
- 16 PROVIDE 3/4" x 4'-0" x 4'-0" FIRE TREATED PLYWOOD TELEPHONE MOUNTING BOARD. PAINT TELEPHONE MOUNTING BOARD TO MATCH ADJACENT PARTITION. TOP OF TELEPHONE MOUNTING BOARD SHALL ALIGN WITH THE TOP OF DOOR FRAME.
- 17 SERVICE ENTRY SECTION- SEE ELECTRICAL DRAWINGS
- 18 4" DIAMETER x 6'-0" CONCRETE FILLED PIPE BOLLARD- PAINT SAFETY YELLOW
- 19 PAINTED 3'-0"x7'-0" HOLLOW METAL DOOR
- 20 6'-0"x8'-0" HOLLOW METAL DOOR