

**CUSTOM BRAND COLOR - PER OWNER** 

## **GENERAL NOTES - ELEVATIONS**

- EXTERIOR SEALANT SHALL MATCH COLOR OF CMU
- INSTALL CONTROL JOINTS PER MFR RECOMMENDATIONS.
- ALL SIGNAGE WILL BE PERMITTED SEPARATELY.
- D COORDINATE ANY REQUIRED KNOX BOXES WITH SHJ/FIRE MARSHALL FOR TYPE AND
- BLOCK SURFACE LX01 SERIES, (50-100 SQ FT/GAL) 1ST COAT: S-W LOXON SELF CLEANING ACRYLIC COATING-SATIN, LX14-50 SERIES.

E PRIME ALL CMU BEFORE PAINTING OR INSULLATION OF OTHER FINISHES WITH LOXON

- 2ND COAT: S-W LOXON SELF CLEANING ACRYLIC COATING-SATIN, LX14-50 SEIRES (530-7.0 MILS WET, 2.0-2.8 DRY PER COAT).
- F ALL EXTERIOR METALWORK, NOT GALVANIZED, SHALL BE PRIMED AND PAINTED WITH 2 COATS OF EXTERIOR ENAMEL PAINT. (LINTELS, BOLLARDS, ETC.)
- G GC SHALL VERIFY LOCAL JURISDICTION AND WIND SPEED REQUIREMENTS TO DETEMINE IF HURRACANE RATED HIGH IMPACT STOREFRONT OR SIGNAGE IS REQUIRED. FURNISH AS REQUIRED.



**METAL** -WALL PANEL



SW 7025 Backdrop

SW 9173 Shiitake Mellow Mauve SPLIT FACE

CMU -SMOOTH **BRICK** -**NATURAL** 

EXTERIOR COLORS AND FINISHES, REFER TO A401

pathangay architects 727 E BETHANY HOME RD SUITE D225, PHOENIX ARIZONA, 85014

(P) 602-368-9375, (F) 602-368-9380



Consultant ID

Sun

Ν

Project Number

2025.05

Issue Date

Drawn By

Reviewed By

Material Board

A403

1/4" = 1'-0"