



**Every LED Outdoor Ceiling  
EYVW Series**

**Features**  
This outdoor LED light is ideal for security and general lighting. Provides lighting in residential, commercial, and hospitality applications. Fixture mounts to standard junction box (not included).

**Construction**  
Die-cast aluminum construction. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

**Finish**  
Black or powder coated or Satin Nickel finish.

**Diffuser**  
Frosted glass diffuser.

**Electrical**  
Input 120-277 VAC 60 / HZ.  
Dimmable with 0-10V dimmers.  
Minimum starting temp -4°F / -20°C.


**Lamping**  
Fixture includes a LED module capable of producing:  
12W = 1000 delivered lumens  
Selectable 3000K, 3500K, 4000K (CCT).  
Rated for 50,000 Hrs., 90 CRI.

**Certification**  
All fixtures are cETLus listed for wet locations.  
Title 24/JAB Compliant.

**Warranty**  
Limited warranty. This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIGURE TYPE
CATALOG NUMBER	



**CLB-4020** **Bollard LED Lighting**

The Decorative Design of the CLB-4020 will assist in enhancing the appearance of any location. It is available in multiple finishes to choose from in order to suit desired requirements. CLB-4020 is commonly installed in exterior facilities (but also works for interior locations) such as: public parks, shopping plazas, walkways, exterior business facilities and residential areas.

**Warranty:**  
-10 year/100,000 hour. Limited Warranty.

**Features:**  
- Energy Savings: Over 66% compared to HID light sources.  
- Improved lumen maintenance.  
- Utilizes High efficient Lumileds LEDs.  
- Operating Temperatures: -30°C ~ 60°C.  
- Driver: 120-277V (ITV).  
- IP65 Rated.  
- 0-10V Dimming Driver, Button Photo Cell or Micro Wave Sensor (Optional).

**Construction:**  
- Corrosion-Resistant Aluminum Housing  
- 3 Mill Powder Coat Finish.  
- Optic Acrylic Lens (Standard)  
- Silicone Gasket to provide Weather-Tight Protection (IP65).  
- Mounting: 3/8" x 18" long Anchors (4x Set)



Example: CLB-4020-36-20CLED-T5-40K-ITV-BR2-360CIP-C

**CLP-BELL** **Architectural LED Luminaire**

CLP-BELL Architectural LED Luminaire, suitable for wet locations. Perfect for lighting up Commercial Exteriors, Walkways, Perimeters, School Campuses, Industrial Spaces, Parking Lots, Recreational Parks.




- Dark Sky compliant  
- 10 Year /100,000 warranty.

**Features:**  
- Energy Savings: Over 66% compared to HID light sources  
- Improved lumen maintenance  
- Utilizes High efficient Lumileds LEDs  
- Operating temperatures: -30°C ~ 60°C  
- Driver: Constant current, 120-277v or, 480v (Optional)  
- 10kv Surge Protector. (standard)  
- 0-10V Dimming, Button Photo Cell or wireless controls (optional)

**Construction:**  
- Housing: Heavy Gauge Spun Aluminum.  
- Cast Aluminum top for additional support.  
- Mounting (Ht): Over 3" O.D. Tennon or Pole.  
- 3 Mill Powder Coat Finish.  
- Clear Optic System.



Example: CLP-BELL-T1-TP1-SH3-RIT1-50CLED-30K-ITV-BR2-HSS



**SCHEDULES:**

Luminaire Schedule						
Symbol	Qty	Label	LLF	Description	Luminaire Watts	Mtg Ht
	3	B1	0.950	CLB-4020-42-20W-T5-3000K-MV-BZ	20	3.5
	4	C1	0.950	LATTICE CYLND-AFX-EVTW-0405LAJD2BK	11	8
	1	S1	0.950	CLP-BELL-L-TP1-SH3-AM-T4-3000K	100	14
	1	W1	0.950	WM-CL-13S-SDB-T-BC-20-3000K	20	6
	2	W2	0.950	GOOSE NCK-GILW1210LAJENBK-3000K	75	9

Calculation Summary							
Label	CalcType	Units	Avg	Max	Min	Avg/Min	Max/Min
SITE CALCS	Illuminance	Fc	0.90	25.0	0.0	N.A.	N.A.

CLAYTON HOMES MESA

