ELECTRICAL SYMBOL LEGEND SOME SYMBOLS AND ABBREVIATIONS MAY NOT BE USED FOR THIS PROJECT.

DOUBLE FACE EXIT SIGN. SEE LIGHTING FIXTURE SCHEDULE FOR SPECIFICATION.

DUAL HEAD EMERGENCY BATTERY PACK, SEE LIGHTING FIXTURE SCHEDULE

CONTACTOR - FURNISHED/INSTALLED BY ELECTRICAL CONTRACTOR SIZE AS NOTED

MOTOR STARTER/CONTROLLER — FURNISHED/INSTALLED BY ELECTRICAL CONTRACTOR.

DISCONNECT SWITCH - SIZE AND FUSES AS PER MANUFACTURER'S RECOMMENDATIONS

COMBINATION FUSIBLE DISCONNECT/MOTOR CONTROLLER - 30/3P WITH MIN. SIZE 1

 $f b_{\sf M}$ horsepower rated manual motor starter with thermal overload(s). Overload

FIRE ALARM HORN/STROBE: +80" AFF OR 6" BELOW CEILING, WHICHEVER IS LOWER.

HEATERS TO BE SIZED PER HORSEPOWER AND MANUFACTURER'S REQUIREMENTS

MAGNETIC STARTER (UNLESS NOTED OTHERWISE). PROVIDE FUSES PER

FIRE ALARM STROBE: +80" AFF OR 6" BELOW CEILING, WHICHEVER IS LOWER.

WEATHERPROOF WHERE OUTSIDE). N.F. INDICATES NON-FUSED

MANUFACTURER'S REQUIREMENTS, N.F. INDICATES NON-FUSED.

ECTIONAL ARROW AS INDICATED ON PLANS (CEILING OR WALL)

E. MECHANICAL

F. FIRE ALARM

B FIRE ALARM BELL

F FIRE ALARM PULL STATION AT +48".

D FIRE ALARM MAGNETIC DOOR HOLDER

FAAP FIRE ALARM ANNUNCIATOR PANEL

FACP FIRE ALARM CONTROL PANEL

(H) FIRE ALARM HEAT DETECTOR

S FIRE ALARM SMOKE DETECTOR.

(C) CARBON MONOXIDE DETECTOR.

FIRE ALARM FLOW SWITCH.

BREAKER AS INDICATED.

H. SECURITY

KP LOW VOLTAGE KEYPAD

SURVEILLANCE CAMERA

A AMPFRF

C CONDUIT

D DEDICATED

F FXISTING

EC EMPTY CONDUIT

EF EXHAUST FAN

EG EQUIPMENT GROUND

AL ALUMINUM

FUSED SWITCH.

≪□ PULLOUT FUSE

(S) SPEAKER

(D) FIRE ALARM DUCT SMOKE DETECTOR.

FIRE ALARM TAMPER SWITCH.

G. ONE LINE DIAGRAM

(M) METER, (S) SOCKET, (B) BLANK, WITH CURRENT TRANSFORMERS.

INTO ACCESSABLE CEILING SPACE

I. ABBREVIATIONS

AIC AVAILABLE INTERRUPTING CURRENT

AFCI ARC FAULT CIRCUIT INTERRUPTER

APS ARIZONA PUBLIC SERVICE - (UTILITY CO.)

AFC AVAILABLE FAULT CURRENT

AFF ABOVE FINISHED FLOOR

AFG ABOVE FINISHED GRADE

CCT CORRECTED COLOR TEMP.

CRI COLOR RENDERING INDEX

DP DUST - IGNITION PROOF

EDF ELECTRIC DRINKING FOUNTAIN

GFP GROUND FAULT PROTECTION

GND GROUND/BOND CONDUCTOR

GWH GAS WATER HEATER

IAW IN ACCORDANCE WITH

MCB MAIN CIRCUIT BREAKER

MCC MOTOR CONTROL CENTER

R EXISTING TO BE RELOCATED

SES SERVICE ENTRANCE SECTION

TEP TUCSON ELECTRONIC POWER

TTC TELEPHONE TERMINAL CABINET

UFER CONCRETE ENCASED ELECTRODE

UNO UNLESS NOTED OTHERWISE

WP WEATHERPROOF (RAIN TIGHT)

NEMA 3R OR NEMA 4 IN-USE

WEATHER RESISTANT

X EXISTING TO BE REMOVED

WR WEATHER RESISTANT

XP EXPLOSION PROOF

IG ISOLATED GROUND

MLO MAIN LUG ONLY

N NEW ITEM

PNL PANELBOARD

SWBD SWITCHBOARD

UG UNDERGROUND

VA VOLT AMPERES

WG WIRE GUARD

WH WATER HEATER

W WATT

EM EMERGENCY LIGHT. BYPASS LOCAL

GFCI GROUND FAULT CIRCUIT INTERRUPTER

SWITCHING AND PROVIDED BATTERY PACK.

NR NEW LOCATION OF RELOCATED EXISTING ITEM

NL NIGHT LIGHT. BYPASS LOCAL SWITCHING.

SRP SALT RIVER PROJECT - (UTILITY CO.)

TMB 3/4" PLYWOOD TELEPHONE MOUNTING

(SIZE INDICATED ON DRAWINGS)

BOARD WITH #6 CU. SOLID GROUND.

AH AIR HANDLER UNIT

BREAKER WITH SHUNT TRIP (SIZE AS INDICATED)

LOW VOLTAGE CARD READER WITH 3/4" EMPTY CONDUIT STUBBED

(M) (M) METER, (S) SOCKET, (B) BLANK

CONTACTOR - FURNISHED AND INSTALL BY OTHERS

MOTOR - SIZE AS INDICATED ON DRAWINGS.

MOTOR STARTER/CONTROLLER- FURNISHED WITH MOTOR.

A. GENERAL

JUNCTION BOX (4" SQUARE MINIMUM)

INDICATES HOMERUN.

LONG DASH INDICATES NEUTRAL CONDUCTOR, SHORT DASH INDICATES PHASE

ISOLATED GROUNDING CONDUCTOR. GREEN, INSULATED WITH YELLOW STRIPE.

GROUNDING CONDUCTOR. GREEN, INSULATED, SIZE PER PLAN.

SURFACE PANELBOARD

FLUSH PANELBOARD

TRANSFORMER. (KVA SIZE AS NOTED). GROUNDING SYSTEM TO BUILDING STEEL (IF APPLICABLE).

. CONDUIT STUB-UP ABOVE CEILING

. CONDUIT STUB-DOWN TO FLOOR BELOW

— — CONDUIT IN UNDERGROUND/SLAB

 □──── CONDUIT STUB-UP WITH CAP CONDUIT SEAL-OFF

9 FLEXIBLE CONDUIT. PROVIDE LIQUID TIGHT FLEX IN WET OR EXTERIOR LOCATIONS AND AT CONNECTIONS TO VIBRATING EQUIPMENT AND/OR TRANSFORMERS. ----- CONDUIT CONCEALED IN WALLS OR ABOVE CEILING.

B. POWER

← 20A SPEC GRADE SINGLE RECEPTACLE MOUNTED AT +15" TO BOTTOM OR AS NOTED

€ 20A SPEC GRADE DUPLEX RECEPTACLE MOUNTED AT +15" TO BOTTOM OR AS NOTED 4 20A SPEC GRADE FOURPLEX RECEPTACLE MOUNTED AT +15" TO BOTTOM OR AS NOTED

20A SPEC GRADE DUPLEX CONVENIENCE OUTLET MOUNTED ABOVE COUNTER.

20A SPEC GRADE FOURPLEX CONVENIENCE OUTLET MOUNTED ABOVE COUNTER.

SPECIAL OUTLET AS NOTED ON DRAWINGS - VERIFY NEMA RATING BEFORE INSTALLATION

SPECIAL OUTLET AS NOTED ON DRAWINGS - MOUNTED IN CEILING RF - REFRIGERATOR

SD - SINK DISPOSAL, PROVIDE SWITCH ABOVE COUNTER. DW - DISHWASHER MW - MICROWAVE - UNDERCOUNTER REFRIGERATOR P - PEDISTAL MOUNTED VM - VENDING MACHINE

SOLATED GROUNDING OUTLET AT +15" TO BOTTOM OR AS NOTED. "LEVITON" #5362-IG (ORANGE) RECEPTACLE WITH ISOLATED GROUND.

€ 20A SPEC GRADE HALF SWITCHED DUPLEX RECEPTACLE AT +15" TO BOTTOM OR AS NOTED. DUAL COMPARTMENT POWER/TELE DATA POLE

FLUSH FLOOR POWER OUTLET WITH FLUSH-IN-USE COVERS - WITH 20A SPEC GRADE RECEPTACLES DUPLEX OR FOURPLEX. HUBBELL, THOMAS & BETTS, CARLON OR EQUAL.

RATED FOR SCRUB WATER. 20A SPEC GRADE GFCI DUPLEX RECEPTACLE AT +15" TO BOTTOM OR AS NOTED.

20A SPEC GRADE GFCI DUPLEX RECEPTACLE AT +6" ABOVE COUNTER TO BOTTOM OR AS NOTED. DROP CORD POWER OUTLET - WITH 20A SPEC GRADE RECEPTACLES DUPLEX OR FOURPLEX.

"J" BOX FLUSH MOUNTED IN WALL FOR SYSTEMS FURNITURE POWER, COORDINATE EXACT LOCATION AND REQUIREMENTS WITH SUPPLIER PRIOR TO ROUGH-IN. ELECTRICAL CONTRACTOR S RESPONSIBLE FOR FINAL CONNECTION TO SYSTEM FURNITURE.

WIRE MOLD. LENGTH AND TYPE AS NOTED ON DRAWINGS. MOUNT AS NOTED ON THE

C. COMMUNICATIONS

FLUSH FLOOR COMBINATION TELEPHONE/DATA OUTLET - PROVIDE 1" MIN CONDUIT TO BOVE ACCESSIBLE CEILING. HUBBELL, THOMAS & BETTS, CARLON OR EQUAL. RATED FOR

DATA OUTLET AT +15" A.F.F. TO BOTTOM OF WALL FIXTURE OR AS NOTED. ROVIDE 3/4" CONDUIT STUBBED TO +4" ABOVE FINISHED CEILING.

TELEPHONE OUTLET AT +15" A.F.F. TO BOTTOM OF WALL FIXTURES OR AS NOTED PROVIDE 3/4" CONDUIT STUBBED TO +4" ABOVE FINISHED CEILING OR AS NOTED

P - PAY PHONE L PHONE OUTLET MOUNTED AT +44" A.F.F.

COMBINATION TELEPHONE/DATA OUTLET AT +15" A.F.F. TO BOTTOM OF WAL FIXTURES OR AS NOTED. PROVIDE 3/4"C. STUBBED TO +4" ABOVE FINISHED CEILING.

DIGITAL CABLE TELEVISION OUTLET

TELEVISION OUTLET WITH DEVICES

"J" BOX FLUSH MOUNTED IN WALL FOR SYSTEMS FURNITURE TELE/DATA WITH 1-1/4" EMPTY CONDUIT STUBBED ABOVE CEILING. COORDINATE EXACT LOCATION AND REQUIREMENTS WITH SUPPLIER PRIOR TO ROUGH-IN. ELECTRICAL CONTRACTOR IS RESPONSIBLE FOR FINAL CONNECTION TO SYSTEM FURNITURE.

TELEPHONE TERMINAL BOARD "TMB". 3/4" PLYWOOD TELEPHONE MOUNTING BOARD WITH #6 COPPER GROUND & DEDICATED FOURPLEX CONVENIENCE OUTLET. FURNISH IN ACCORDANCE WITH TELEPHONE COMPANY'S REQUIREMENTS. SIZE AS NOTED ON DRAWINGS. PLYWOOD SHALL

<u>D. LIGHTING</u>

STANDARD SWITCH AND COVER PLATE WITH LOCKING DEVICE (BRADY NO. 2AF98 OR EQUAL)

SINGLE POLE SWITCH MOUNTED AT +44" TO CENTER OF DEVICE OR AS NOTED.

TWO POLE SWITCH MOUNTED AT +44" TO CENTER OF DEVICE OR AS NOTED. THREE WAY SWITCH MOUNTED AT +44" TO CENTER OF DEVICE OR AS NOTED.

FOUR WAY SWITCH MOUNTED AT +44" TO CENTER OF DEVICE OR AS NOTED.

 $f \$_{ extsf{P}}$ - single pole switch with pilot light at +44" to center of device or as noted.

\$D 2000W SLIDE CONTROL DIMMER AT AT +44" TO CENTER OF DEVICE OR AS NOTED.

LOW VOLTAGE SLIDE CONTROL DIMMER WITH PRESET AT +44".
CONTRACTOR SHALL SUPPLY SPECIFIC (ELECTRONIC AND/OR MAGNETIC)

\$0S WALL MOUNTED OCCUPANCY SENSOR. LUTRON-DUAL TECHNOLOGY OR EQUAL. IN RESTROOMS: LUTRON-ULTRASONIC. PROGRAM: MANUAL ON/AUTO OFF UNLESS

\$UD SINGLE POLE UP-OFF-DOWN SWITCH FOR CONTROL OF PROJECTION SCREEN. MOUNTED AT +44" TO CENTER OF DEVICE OR AS NOTED.

LOW VOLTAGE PUSH BUTTON CONTROL STATION AS NOTED. VERIFY MOUNTING HEIGHT.

ROOF MOUNTED PHOTOCELL (AIM NORTH) INTERMATIC #EK4136S OR EQUAL. ASTRONOMIC ELECTRONIC 4 POLE LIGHTING TIMESWITCH, INTERMATIC #ET2845CR OR EQUAL.

©S CEILING MOUNTED OCCUPANCY SENSOR 360°. LUTRON-DUAL TECHNOLOGY OR QUAL. IN RESTROOMS: LUTRON-ULTRASONIC. IN WAREHOUSE

LUTRON-HIGHBAY. (WR) WIDE ANGLE (LR) LONG RANGE. WALL/CEILING MOUNTED DUAL TECHNOLOGY OCCUPANCY SENSOR SHALL BE

PROGRAMMED AS VACANCY SENSOR. MANUAL ON/AUTO OFF. POCCUPANCY SENSOR - POWER PACK OR SLAVE PACK.

► LED STRIP LIGHTING FIXTURE — AS NOTED ON DRAWINGS. O LED LIGHTING FIXTURE - AS NOTED ON DRAWINGS SURFACE MOUNTED.

RECESSED GRID W/FLEXIBLE CONNECTION. INDICATES NIGHTLIGHT (NL) AND/OR EMERGENCY FIXTURE WITH 1400 LUMEN MINIMUM (UNSWITCHED) — AS NOTED ON DRAWING.

 $oldsymbol{Q}$ Wall mounted lighting fixture — as noted on drawings.

CEILING MOUNTED LIGHTING FIXTURE - AS NOTE ON DRAWINGS.

LED HIGH/LOW BAY FIXTURE

WALL WASH LIGHTING FIXTURE. AIM AS DIRECTED BY ARCHITECT.

TRACK LIGHTING SYSTEM WITH TRACK FIXTURE HEADS AS INDICATED ON PLANS. VERIFY TYPE LINE OR LOW VOLTAGE. \P POLE MOUNTED AREA LIGHT (ARM MOUNTED) VERIFY HEIGHT SEE POLE DETAIL.

POLE MOUNTED AREA LIGHT (POST TOP) VERIFY HEIGHT SEE POLE DETAIL.

SINGLE FACE EXIT SIGN, SEE LIGHTING FIXTURE SCHEDULE FOR SPECIFICATION. DIRECTIONAL ARROW AS INDICATED ON PLANS (CEILING OR WALL.)

COMBINATION EMERGENCY EXIT SIGN WITH DUAL HEAD LIGHTS WITH

SOME SPECIFICATIONS MAY NOT BE USED FOR THIS PROJECT.

ELECTRICAL SPECIFICATIONS

1.0 INTENT FURNISH AND INSTALL A COMPLETE AND OPERATIONAL ELECTRICAL SYSTEM IN ACCORDANCE WITH PLANS AND SPECIFICATIONS.
ALL DRAWINGS ARE SCHEMATIC IN NATURE AND THE REQUIRED INSTALLATION IS NOT LIMITED TO WHAT IS SHOWN. ALL APPURTENANCES NECESSARY TO PROVIDE A COMPLETE AND OPERATIONAL SYSTEM MUST BE INCLUDED IN THE CONTRACTORS BID

2.0 GENERAL

THE CONTRACTOR SHALL VISIT THE JOB SITE AND FAMILIARIZE HIMSELF WITH ALL EXISTING CONDITIONS WHICH MAY AFFECT HIS BID OR WORK. NO ALLOWANCES WILL BE MADE FOR EXISTING CONDITIONS OR THE CONTRACTORS FAILURE TO ACCOMMODATE STING CONDITIONS ON HIS BID. EXISTING CONDITIONS ON HIS BIID.
IT IS THE CONTRACTORS RESPONSIBILITY TO OBTAIN CLARIFICATION OF ANY APPARENT CONFLICT OR INCONSISTENCY IN THE DRAWINGS, SPECIFICATION, OR DESIGN, PRIOR TO

HIS BID AND IN WRITING WITH THE ENGINEER. OTHERWISE THE CONTRACTOR ACCEPTS RESPONSIBILITY TO CORRECT (AT HIS COST) ANY SUCH ITEMS TO MEET THE INTENT S INTERPRETED BY THE ENGINEER AS INTERFRIED BY THE ENGINEER.
ALL MATERIAL AND WORKMANSHIP SHALL CONFORM TO THE MOST RECENT ADOPTED EDITIONS OF THE NFPA, NATIONAL ELECTRIC CODE, IBC, APPLICABLE CITY AND STATE CODES AND ORDINANCES, THE AMERICANS WITH DISABILITIES ACT, E.P.A. REGULATION: INCLUDING EPACT 1992). INTERNATIONAL ENERGY CONSERVATION CODE (IECC)/TITLE 4/ASHRAE 90.1 AND UTILITY COMPANY REQUIREMENTS. THE FOREGOING CODES AND EGULATIONS ARE REQUIREMENTS AND ARE INCORPORATED IN THIS SPECIFICATION FOR

THIS WORK BY REFERENCE.

THE CONTRACTOR SHALL COORDINATE AND PROVIDE INFORMATION AS REQUIRED TO ALL SERVING UTILITIES IN A TIMELY MANNER AS NECESSARY TO PROVIDE THE SERVICE REQUIRED AND MEET UTILITY REQUIREMENTS. IMMEDIATE COORDINATION WILL BE REQUIRED FOR MOST PROJECTS. FIELD COORDINATE ALL REQUIREMENTS WITH Y Co. PRIOR TO TRENCHING.

REFER TO ARCHITECTURAL, MECHANICAL, CIVIL, STRUCTURAL, AND/OR EQUIPMENT SUPPLIERS DRAWINGS AND SPECIFICATIONS FOR EXACT EQUIPMENT LOCATIONS, LOADS AND ADDITIONAL REQUIREMENTS. REPRESENTATIONS OF THE WORK SPECIFIC TO THE OTHER DISCIPLINES IS SHOWN ON THE ELECTRICAL DRAWINGS FOR CLARITY ONLY.
THE CONTRACTOR ASSUMES RESPONSIBILITY FOR ALL EQUIPMENT HE SUPPLIES. ALL
EQUIPMENT SHALL BE INSTALLED STRICTLY PER MANUFACTURERS RECOMMENDATIONS. OTHERWISE THE CONTRACTOR ASSUMES RESPONSIBILITY (AT HIS COST) TO CORRECT ND REMEDY ANY INSTALLATION NOT IN COMPLIANCE WITH THE MANUFACTURES RECOMMENDATIONS AND INTENTIONS AS INTERPRETED BY THE ENGINEER.

ANY VARIANCE OR EXCEPTIONS TO THE DRAWINGS AND SPECIFICATIONS MUST BE

REQUESTED AND APPROVED IN WRITING. INTERIM VERBAL APPROVALS WILL ONLY I PROVIDED WHEN THE ENGINEER DETERMINES THIS TO BE JUSTIFIED AND MUST BE CONFIRMED IN WRITING TO BE FINAL.
THE CONTRACTOR IS RESPONSIBLE TO OBTAIN ALL NECESSARY PERMITS, VARIANCES, ND APPROVALS, ETC. (AT HIS COST) WHICH MAY BE REQUIRED FOR COMPLETION OF

THIS WORK.
PRIOR TO ROUGH-IN, THE ELECTRICAL CONTRACTOR SHALL COORDINATE THE EXACT OCATION OF ALL LIGHT FIXTURES AND WIRING DEVICES: TO INCLUDE MOUNTING HEIGHT AND LOCATIONS WITH ARCHITECT/OWNER. ALL CONFLICTS SHALL BE REPORTED O THE ENGINEER/ARCHITECT THE ELECTRICAL CONTRACTOR SHALL PROVIDE EQUIPMENT AND SUPPORT FOR PROGRESS AND FINAL INSPECTIONS. THIS INCLUDES COMPLETE ACCESS TO ALL EQUIPMENT. ADDITIONALLY A COMPLETE SET OF SPARE FUSES FOR ALL FUSES USED AND A 5% SUPPLY OF ALL LIGHT BULBS PROVIDED IN FIXTURES (TO A MAXIMUM OF

15 FOR EACH STYLE) SHALL BE PROVIDED TO THE OWNER AT FINAL INSPECTION. RECONSTRUCTION (TO INCLUDE TENANT IMPROVEMENTS). ALL RECONSTRUCTION OF ISTING FACILITIES AND EQUIPMENT SHALL REQUIRE COMPLETE RENOVATION (MAKE GOOD AS NEW) FOR ALL EXISTING EQUIPMENT UPON WHICH WORK IS PERFORMED OR EQUIPMENT WHICH IS AFFECTED BY THE WORK PERFORMED. THIS WILL INCLUDE THESE FOLLOWING REQUIREMENTS: 2.11.1 VERIFICATION OF EXISTING SES COMPLIANCE WITH NEC "GROUNDING" VERIFICATION OF CABLE SIZE AND AMPACITY OF EXISTING FEEDERS AND BRANCH CIRCUITS WITH NEC TABLES.
2.11.3 EXISTING LIGHT FIXTURES TO BE REUSED MUST BE CLEANED, RE-LAMPED, AND RESTORED TO "LIKE NEW" CONDITION. AND RESTORED TO LIKE NEW CONDITION.
2.11.4 EXISTING PANEL BOARDS, SWITCH BOARDS, AND TRANSFORMERS WHICH ARE NCLUDED IN THE PROJECT WORK SHALL HAVE PREVENTATIVE MAINTENANCE PERFORMED TO INCLUDE RE-TORQUING OF ALL LUGS, CLEANING AND INSPECTION.
2.11.5 VERIFY PROPER WORKING CONDITION OF ALL EXISTING EMERGENCY FIXTURES AND EXIT SIGNS, REPAIR OR REPLACE AS REQUIRED.

IN THE EVENT THAT INSPECTION REVEALS DISCREPANCIES AND/OR NONCOMPLIANCE HE OWNER AND THE ENGINEER SHALL BE NOTIFIED IN WRITING, AND EQUIPMENT BROUGHT INTO COMPLIANCE

3.0 MATERIALS AND METHODS

THE USE OF EMT IS ACCEPTABLE IN ACCORDANCE WITH NEC ARTICLE "ELECTRICAL METALLIC TUBING". EMT SHALL NOT BE USED WHERE IT IS SUBJECT TO SEVERE PHYSICAL DAMAGE. EMT FITTINGS SHALL BE COMPRESSION TYPE. MINIMUM TRADI CONDUIT SIZE IS 1/2" AND 3/4" FOR HOME RUNS.

CONDUCTORS SHALL BE 600V COPPER (98 % CONDUCTIVITY). MINIMUM LINE VOLTAGE WIRE SIZE IS #12 A.W.G. #6 AND SMALLER SHALL HAVE THHN/THHW INSULATION. #4 AND LARGER SHALL HAVE XHHW/XHHW-2 INSULATION. ALL CONDUCTORS SHALL HAVE 90° RATED INSULATION. ALL 120V. 20A BRANCH CIRCUIT CONDUCTORS (#12) OVER 100' IN LENGTH TO BE #10'S MINIMUM. ALL 277V, 20A BRANCH CIRCUIT CONDUCTORS (#12) OVER 200' IN LENGTH TO BE #10'S MINIMUM.
WHEN SEPARATE BRANCH CIRCUIT NEUTRAL CONDUCTORS ARE USED WITH EACH PHASE CONDUCTOR OR SYSTEMS FURNITURE IS INDICATED, THE MINIMUM NEUTRAL

ONDUCTOR SIZE SHALL BE #10 A.W.G. STRANDED COPPER. ALL WIRING DEVICES SHALL BE SPECIFICATION GRADE. (MINIMUM 20 AMPS RATED FOR RECEPTACLES AND SWITCHES). HUBBELL, PASS & SEYMOUR, BRYANT, OR LEVITON ARE ACCEPTABLE. ALL SPECIAL RECEPTACLES AND GROUND FAULT PROTECTION DEVICES MUST BE PERMANENTLY MARKED WITH ENGRAVED COVER PLATES. INDICATE USE AND CIRCUIT NUMBER.

COVER PLATES AND DEVICES SHALL BE PHENOLIC PLASTIC (WHITE OR COLOR ELECTED BY ARCHITECT) IN OFFICE/COMMERCIAL/OR LIVING AREAS, AND GALVANIZED STEEL IN WAREHOUSE/INDUSTRIAL/MANUFACTURING AREAS OR AREAS SUBJECT TO ALL CONDUCTORS TO BE CONCEALED EXCEPT TO SURFACE MOUNTED PANELS AND AT THE CEILING OF EXPOSED STRUCTURE AREAS. CONDUITS WILL BE RUN PARALLEL OR RPFNDICULAR TO BUILDING LINES.

FLEXIBLE METAL CONDUIT (SEAL TITE FOR EXTERIOR APPLICATIONS) SHALL BE USED FOR CONNECTIONS TO EQUIPMENT SUBJECT TO VIBRATION (E.G. MOTORS) WITH A MAX. THE USE OF MC CABLE IS ACCEPTABLE (UPON OWNER NOTIFICATION AND APPROVAL) AND MAY BE USED IN ACCORDANCE WITH NEC ARTICLE "METAL-CLAD CABLE: TYPE C", BUT LIMITED TO USE FOR CONCEALED BRANCH CIRCUITS ONLY, ADDITIONALLY MC <u>CABLE MAY NOT</u> BE USED FOR HOME RUNS OR OUTDOORS.

NON-METALLIC CONDUIT (MIN. SCHEDULE 40) MAY BE USED ONLY IN OR UNDER SLABS & IN CONCRETE OR MASONRY WALLS. MIN. 24" COVER REQUIRED FOR FUSES SHALL BE BUSSMAN, LITTLEFUSE, OR GOULD SHAWMUT.
CONDUCTORS WILL BE SOLID AND/OR STRANDED WITH INSULATION CONTINUOUSLY

COLOR COATED UP TO AND INCLÚDING SIZE #6 A.W.G. GROUNDING/BONDING CONDUCTORS SHALL BE U.L. LABELED ROPE STRAND CONNECTIONS OR SPLICES SHALL BE EXOTHERMIC WELD (CAD WELD OR THOMAS AND BETTS FURSEWELD) FOR GROUNDING/BONDING CONDUCTORS.

CONNECTIONS ARE EXCEPTIONS AND REQUIRE SPECIFIC APPROVAL IN WRITING B HAWKINS DESIGN GROUP. ALL CONDUIT SUPPORT SYSTEMS SHALL BE INSTALLED ON THE BUILDING STRUCTURE. UNISTRUT, BEELINE, SUPERSTRUT STEEL CITY SPRING STEEL FASTENERS OR CADDY MOUNTING SYSTEMS ARE ACCEPTABLE. NO CONDUIT WILL BE SUPPORTED BY THE CEILING WIRES, TIE WIRE OR GRID SYSTEM. PERFORATED STRAPS OR OTHER PIPING

AND CONDUIT STRAPS ARE NOT ACCEPTABLE SUPPORTS.

ACCEPTABLE MANUFACTURES FOR SWITCH GEAR, DISTRIBUTION GEAR AND RELATED COMPONENTS ARE: SQUARE D, ACME TRANSFORMERS, GENERAL ELECTRIC, SIEMENS, HPS, AND CUTLER—HAMMER.

CONDUCTORS SHALL BE COLOR CODED FOR BRANCH CIRCUITS AND PHASE LEGS OF FEEDERS TO PANEL BOARDS, SWITCHBOARDS, ETC. IN ACCORDANCE WITH NEC AND LOCAL MUNICIPAL REQUIREMENTS. SPECIFIC REQUIREMENTS INCLUDE THE FOLLOWING

120-V. 2-WIRE CIRCUIT: GROUNDED NEUTRAL-WHITE; UNGROUNDED LEG-BLACK.
208Y/120-V. 3-PHASE. 4-WIRE: GROUNDED NEUTRAL-WHITE; PHASE A-BLACK;
PHASE B-RED; PHASE C-BLUE. 240/120-V. 3 WIRE, SINGLE PHASE CIRCUIT: GROUNDED NEUTRAL-WHITE; PHASE A-BLACK: PHASE B-RED • 240-V. DELTA, 3-PHASE, 3-WIRE: PHASE A-BLACK; PHASE B-RED; PHASE • 240/120-V, 3-PHASE, 4-WIRE, HIGH-LEG DELTA: GROUNDED

NEUTRAL-WHITE; HIGH LEG (208-V TO NEUTRAL)-ORANGE; PHASE A-BLACK;

480Y/277-V. 3-PHASE, 4-WIRE: GROUNDED NEUTRAL-GRAY; PHASE A-BROWN; PHASE B-ORANGE: PHASE C-YELLOW. 480-V. DELTA, 3-PHASE, 3-WIRE: PHASE A-BROWN; PHASE B-ORANGE; PHASE C-YFLLOW 480-V. DELTA, 3-PHASE, 3-WIRE: PHASE A-BROWN; PHASE B-ORANGE; PHASE EQUIPMENT GROUNDING CONDUCTORS-GREEN; ISOLATED GROUNDS-GREEN WITH A ALL INSTALLATIONS WITHIN PLENUM RATED CEILING SPACE SHALL BE IN ACCORDANCE MITH NEC ARTICLE "WIRING METHODS" WITH REGARDS TO SMOKE DEVELOPMENT AND

FLAME SPREAD. ALL UNDERGROUND CABLE, PIPE AND CONDUITS SHALL BE DETECTABLE (METALLIC) OR HAVE A DETECTABLE UNDERGROUND LOCATION DEVICE INSTALLED WITH IT. THE RECOMMENDED DETECTABLE UNDERGROUND LOCATION DEVICE IS A #18 OR LARGER COPPER TRACER WIRE SECURELY ATTACHED TO THE TOP OF ANY NON-METALLIC RACER WIRE ACCESSIBLE AT ALL ABOVE GRADE TERMINATIONS. ALL HORIZONTAL UNDERGROUND CONDUIT RUNS (INCLUDING UNDER CONCRETE SLABS)

ALL MATERIAL & DEVICES USED EXTERIOR OF THE BUILDING SHALL BE LISTED U.L. FOR WATERPROOF APPLICATIONS.

SHALL BE A MINIMUM OF 24" BELOW GRADE.

4.0 SUBMITTALS SUBMIT 6 SETS OF SHOP DRAWINGS AND SAMPLES FOR ALL EQUIPMENT PRIOR TO ORDERING IN A TIMELY MANNER, SUBMITTALS SHALL INCLUDE LIGHT FIXTURES (INCLUDING LIGHT POLES), LIGHTING CONTROLS, SWITCHBOARDS, PANELBOARDS, BREAKERS, STARTERS, HVAC ELECTRICAL EQUIPMENT AND TRANSFORMERS. SHOP DRAWINGS SHALL INCLUDE LAYOUT DIMENSIONS AND IDENTIFICATION SPECIFIC EQUIPMENT FOR INSTALLATION, MINIMUM NEC CLEARANCES SHALL BE

THE CONTRACTOR SHALL INCLUDE COMPARISON DATA AND SAMPLES FOR BOTH THE SUBSTITUTE AND SPECIFIED ITEMS WHEN SUBSTITUTIONS ARE PROPOSED THE CONTRACTOR REMAINS RESPONSIBLE TO PROVIDE THE ORIGINALLY SPECIFIED INSTALLATION IN ACCORDANCE WITH THE ORIGINAL DELIVERY DATE (AT HIS COST) INSTALLATION IN ACCORDANCE WITH THE ORIGINAL DELIVERY DATE (AT HIS COST)
WHEN SUBSTITUTIONS ARE NOT APPROVED.
THE CONTRACTOR SHALL PROVIDE PROOF OF PERFORMANCE BOND WITH HIS INITIAL SUBMITTALS (E.G. SHOP DRAWINGS) TO INCLUDE WARRANTY FOR THE WARRANTY

THE CONTRACTOR SHALL SUBMIT COMPLETE AND ACCURATE "AS BUILT" DRAWING TO THE OWNER AND ENGINEER WITHIN 2 WEEKS OF OWNER ACCEPTANCE. PROVIDE 4 SETS OF BLUELINES OR REPRODUCIBLES. FAILURE TO COMPLY WILL RESULT IN WITHHOLDING OF PAYMENTS DUE, AND ASSESSMENT OF CHARGES (AGAINST THE CONTRACTOR) FOR AS-BUILT DEVELOPMENT BY THE ENGINEER AT THE CURRENT HOURLY RATE. PROVIDE A LETTER TO THE OWNER AND ENGINEER CERTIFYING ALL EQUIPMENT AND TERMINATION'S ARE PROPERLY TORQUED. THIS CERTIFICATION SHALL BE EXECUTED BY LICENSED CONTRACTOR, AND WRITTEN CERTIFICATION PROVIDED ON COMPANY

PROVIDE 2 COPIES OF ALL MANUFACTURER/SUPPLIER WARRANTIES AND GUARANTEES TO THE OWNER WITHIN 2 WEEKS OF FINAL ACCEPTANCE BY THE OWNER. POWER DISTRIBUTION SYSTEM AS A COMPLETE PACKAGE TO THE OWNER AND ENGINEER. PACKAGE MUST PROVIDE SPECIFIC VALUES OF TEST DATA OBTAINED AGAINST ACCEPTANCE CRITERIA (SIMPLE PASS/FAIL ALONE IS INADEQUATE). TESTING PERSONAL SHALL BE CERTIFIED BY THE NATIONAL ELE TESTING ASSOCIATION (NETA) OR NATIOANL INSTITUTE FOR CERTIFICATION IN ENGINEERING TECHNOLOGIES (NICET)

4 HOURS AFTER RAINFALL

4.6.6.4

OVER-POTENTIAL (HI-POT) TESTIN

ALL TESTING SHALL BE DONE IN ACCORDANCE WITH MANUFACTURER RECOMMENDATIONS OR NATIONALLY RECOGNIZED STANDARDS AND PRACTICES GROUNDING SYSTEM FALL OF POTENTIAL (RESISTANCE TO GROUND) TESTING. 4.6.4.1 GROUND SHALL PROVIDE 5 OHMS OR LESS RESISTANCE TO GROUND AND LESS THAN 0.5 OHMS POINT-TO-POINT BETWEEN THE MAIN GROUNDING ELECTRODE SYSTEM AND ELECTRICAL EQUIPMENT FRAMES SYSTEM NEUTRAL AND/OR DERIVED NEUTRAL POINTS (REFERENCE IEEE STANDARDS 81-1983 AND 81-1991) AND SHALL NOT BE PERFORMED WITHIN

4.6.5.1 SHALL BE PERFORMED ON ALL BUSSES 1000A OR GREATER OR ON MODIFICATIONS OF SERVICES GREATER THAN 400 AMPS. 16.5.2 TEST BOTH PHASE-TO-PHASE AND PHASE-TO-GROUND FOR AT LEAST ONE MINUTE. GROUND FAULT PROTECTION TESTING 4.6.6.1 PROVIDE GROUND-FAULT PROTECTION TESTING BY CURRENT INJECTION AT SENSOR. TEST PRIMARY CONTROL VOLTAGE TO NOT EXCEED 57% OF THE 4.6.6.3 VERIFY PICK-UP TIME AND TIME-DELAY SETTINGS PROVIDED BY

INSULATION RESISTANCE (MEGGER) TESTING 4.6.7.1 TESTING SHALL BE 1000 VOLTS FOR ONE MINUTE AND SHALL PROVIDE 50 MEGAOHMS RESISTANCE OR GREATER. TEST BOTH PHASE-TO-PHASE AND PHASE-TO-GROUND.

TEST INTEGRITY OF GROUNDED CONDUCTOR AND ITS INSULATION

5.0 WARRANTY

THE CONTRACTOR SHALL GUARANTEE ALL MATERIAL AND FOR WORKMANSHIP FURNISHED BY HIM UNDER THIS CONTRACT FOR A PERIOD OF TWO YEARS FROM THE DATE OF FINAL ACCEPTANCE OF THE WORK BY THE OWNER. ANY DEFECTS DEVELOPING DURING THE WARRANTY PERIOD TRACEABLE TO MATERIALS OR WORKMANSHIP SHALL BE CORRECTED AT THE CONTRACTORS EXPENSE. THE OWNER RETAINS THE RIGHT TO REQUIRE REMOVAL AND INSTALLATION (AT ANY TIME) OF ANY MATERIAL OR FOUIPMENT NOT IN COMPLIANCE WITH THE PROVISIONS ADDITIONAL COMPENSATION WILL BE ALLOWED FOR WORK PERFORMED IN THIS REGARD. THE CONTRACTOR AGREES TO TRANSFER ALL MANUFACTURER'S/SUPPLIER'S WARRANTIES AND GUARANTEES TO THE OWNER. THIS INCLUDES COMPLETION OF ALL

DOCUMENTATION FOR THE MANUFACTURER/SUPPLIER.

PROVIDE AND INSTALL NEW SERVICE SECTION AS SHOWN ON DRAWINGS. S.E.S. SHALL BEAR U.L. LABEL, HAVE COPPER BUSSING — SILVER PLATED, AND AMPERAGE RATING AS SHOWN ON DRAWINGS. METERING AND PRIMARY PULL SECTION SHALL BE BARRIERED FROM OTHER WORK AND APPROVED BY BOTH THE LOCAL UTILIT COMPANY AND AUTHORITY HAVING JURISDICTION.

GROUND FAULT PROTECTION SHALL BE PROVIDED FOR SERVICES (480V L-L) WITH DISCONNECTS 1000A OR GREATER. GROUND FAULT PROTECTION ON MAINS AND SUB-MAINS MUST HAVE AUDIBLE/VISIBLE ENCLOSURES SHALL MEET U.L. AND PUBLIC UTILITY REQUIREMENTS—PHYSICALLY BARRIERED BETWEEN SECTIONS, LINE AND LOAD, BOTH BARRIERED.

NO COVERS GREATER THAN 1/3 HEIGHT OF FOUIPMENT. FULL SIZED NEUTRAL BUSSING AND FULLY RATED (NON-TAPERED) BUSSING WILL BE STANDARD. THIS INCLUDES MAXIMUM RATINGS FOR SUPPLY AND SECTION (i.e. HORIZONTAL AND VERTICAL) BUSSES (UNLESS NOTED OTHERWISE). CENTER FEED SUPPLY BUSSES SHALL BE MAXIMUM RATED ON EITHER SIDE OF THE FEED. ALL SPACE WILL BE FULLY BUSSED FOR FUTURE. ALL BUSSING WILL BE PHYSICALLY

ALL SERVICES SHALL BE U.L. LISTED FOR FRONT ACCESSIBILITY ONLY.
ALL SERVICE SECTIONS SHALL BE OF A CONSISTENT HEIGHT AND INCLUDE PROTECTION
OF OPERATIONAL DEVICES AND METERS FROM PHYSICAL DAMAGE. PROVIDE CONCRETE HOUSEKEEPING PADS FOR ALL FREESTANDING ELECTRICAL SERVICE ENTRANCE EQUIPMENT PER LOCAL UTILITY COMPANY SPECIFICATIONS. SERVICE COORDINATION STUDY

> 6.10.1.1 WHEN ADJUSTABLE TRIP CIRCUIT BREAKERS OR 2-TIER GROUND FAULT SYSTEM IS SPECIFIED, PROVIDE A SHORT-CIRCUIT AND PROTECTIVE DEVICE COORDINATION STUDY FOR THE ELECTRICAL DISTRIBUTION SYSTEM. THE INTENT OF THESE STUDIES ARE TO VERIFY THAT THE SPECIFIED AND SUPPLIED EQUIPMENT ARE PROPERLY RATED, CORRECTLY APPLIED, AND WITHIN INDUSTRY AND MANUFACTURER'S TOLERANCES. 6.10.1.2 THE SHORT CIRCUIT STUDY SHALL INCLUDE ALL PORTIONS OF THE ELECTRICAL DISTRIBUTION SYSTEM FROM THE NORMAL AND ALTERNATE SOURCES OF POWER THROUGHOUT THE DISTRIBUTION SYSTEM DOWN TO THE SMALLEST PROTECTIVE DEVICE. THE SHORT CIRCUIT STUDY SHALL CONSIDER OPERATION DURING NORMAL CONDITIONS, ALTERNATE OPERATIONS, EMERGENCY POWER CONDITIONS AND ANY OTHER OPERATIONS WHICH COULD RESULT IN MAXIMUM FAULT CONDITIONS. THE COORDINATION STUDY WILL DETERMINE THE CORRECT CAUSED BY AN ELECTRICAL FAULT AND ALLOW FOR SELECTIVE COORDINATION BETWEEN THE DEVICES. THE COORDINATION STUDY SHALL INCLUDE THE CLOSET UPSTREAM UTILITY PROTECTIVE DEVICE DOWN TO THE PANELBOARD MAIN, BRANCH OR FEEDER CIRCUIT BREAKERS, THE CONDITIONS. ALTERNATE OPERATIONS AND DURING EMERGENCY POWER

6.10.2 QUALIFICATIONS 6.10.2.1 THE CONTRACTOR SHALL HAVE THE COORDINATION STUDY PREPARED BY QUALIFIED ENGINEERS OF AN INDEPENDENT CONSULTANT AND OR MANUFACTURER. THE CONSULTANT/MANUFACTURER SHALL BE AN EXPERIENCED REGISTERED PROFESSIONAL FLECTRICAL ENGINEER (LICENSED N THE STATE WHERE THE PROJECT IS COMPLETED) SPECIALIZING IN

PERFORMING POWER SYSTEM STUDIES.

SUBMITTALS

6.10.3.1 THE CONTRACTOR SHALL SUBMIT THE POWER SYSTEM STUDIES IN CONJUNCTION WITH THE EQUIPMENT SUBMITTALS. THE ELECTRICAL SUBMITTALS WILL BE REVIEWED BUT WILL NOT BE APPROVED UNLESS THE POWER SYSTEM STUDIES HAVE BEEN RECEIVED AND REVIEWED. PROTECTIVE DEVICE COORDINATION STUDY

6.11.1 ALL REQUIREMENTS OF THE CURRENT NATIONAL ELECTRICAL CODE AND NFPA 5000 SHALL BE ADHERED TO.
6.11.2 THE COORDINATION STUDY SHALL INCLUDE THE CLOSEST UPSTREAM UTILITY PROTECTIVE DEVICE DOWN TO THE PANELBOARD MAIN, BRANCH, OR FEEDER CIRCUIT BREAKERS. PREPARE THE COORDINATION CURVES TO DETERMINE THE REQUIRED SETTINGS OF PROTECTIVE DEVICES TO ASSURE SELECTIVE COORDINATION. AS WELL AS SETTINGS FOR ALL OTHER ADJUSTABLE PROTECTION SHALL BE INCLUDED, AS WELL AS SETTINGS FOR ALL OTHER ADJUSTABLE PROTECTIVE DEVICES.
6.11.4 GRAPHICALLY ILLUSTRATE ON LOG-LOG PAPER THAT ADEQUATE TIME PARATION EXISTS BETWEEN DEVICES. SUFFICIENT CURVES SHALL CLEARLY INDICATE THE COORDINATION ACHIEVED BETWEEN DEVICES. REASONABLE

COORDINATION INTERVALS AND SEPARATION OF CHARACTERISTIC CURVES SHALL BE MAINTAINED. PLOT THE SPECIFIC TIME—CURRENT CHARACTERISTICS OF EACH PROTECTIVE DEVICE IN SUCH A MANNER THAT THE UPSTREAM DEVICES WILL BE CLEARLY DEPICTED ON THE SHEET. THE FOLLOWING SPECIFIC INFORMATION SHALL ALSO BE SHOWN ON THE COORDINATION CURVES:
6.11.5.1 DEVICE IDENTIFICATIONS.
6.11.5.2 TIME AND CURRENT RATIO FOR CURVES.
6.11.5.3 FUSE, CIRCUIT BREAKER, AND RELAY CURVES, SHOWING COMPLETE OPERATING BANDS OF LOW VOLTAGE CIRCUIT BREAKER TRIP CURVES. 6.11.5.4 LOW VOLTAGE EQUIPMENT CIRCUIT BREAKER TRIP DEVICES, INCLUDING MANUFACTURERS TOLERANCE BANDS.

6.11.5.5 PERTINENT TRANSFORMER FULL-LOAD CURRENTS AT 100 AND 600

6.11.5.6 GROUND FAULT PROTECTIVE DEVICE SETTINGS.
6.11.5.7 OTHER SYSTEM LOAD PROTECTIVE DEVICES FOR LARGEST BRANCH CIRCUIT AND FEEDER CIRCUIT BREAKER IN EACH MOTOR CONTROL CENTER ND PANELBOARD 6.11.6 DEVELOP A TABLE TO SUMMARIZE THE SETTINGS SELECTED FOR THE PROTECTIVE DEVICES. INCLUDE IN THE TABLE THE FOLLOWING: 6.11.6.1 DEVICE IDENTIFICATIONS.
6.11.6.2 DURRENT TRANSFORMER RATIO, RELAY TAP, TIME DELAY AND INSTANTANEOUS PICKUP. 6.11.6.3 CIRCUIT BREAKER SENSOR RATING, LONG-TIME, SHORT-TIME AND INSTANTANEOUS SETTINGS AND TIME BANDS.

6.11.6.4 FUSE RATING AND TYPE.
6.11.6.5 GROUND FAULT PICKUP AND TIME DELAY. 6.12 ANALYSIS 6.12.1 ANALYZE THE SHORT CIRCUIT CALCULATIONS AND HIGHLIGHT ANY EQUIPMENT THAT IS DETERMINED TO BE UNDERRATED AS SPECIFIED OR NOT COORDINATED. PROPOSE APPROACHES TO EFFECTIVELY PROTECT THE UNDERRATED EQUIPMENT. PROPOSED MAJOR CORRECTIVE MODIFICATIONS WILL BE TAKEN UNDER ADVISEMENT BY THE ENGINEER AND THE CONTRACTOR WILL BE GIVEN FURTHER

AFTER DEVELOPING THE COORDINATION CURVES, HIGHLIGHT AREAS LACKING COORDINATION, FOR EACH SHEET, PRESENT A TECHNICAL EVALUATION WITH A DISCUSSION OF THE LOGICAL COMPROMISES FOR BEST COORDINATION. HE RESULTS OF THE POWER SYSTEM STUDY SHALL BE SUMMARIZED IN A FINAL REPORT. THE REPORT SHALL INCLUDE THE FOLLOWING SECTIONS:
6.13.1 PROTECTIVE DEVICE TIME VERSUS CURRENT COORDINATION CURVES,
TABULATIONS OF RELAY AND CIRCUIT BREAKER TRIP SETTINGS, FUSE SELECTION AND COMMENTARY REGARDING SAME. COMMENTARY RESAMPLING SAME.

6.13.2 COPIES OF THE MANUFACTURERS TIME CURRENT CURVES FOR THE DEVICES STUDIED AND PLOTTED ON THE TIME CURRENT CURVES.

7.0 DISTRIBUTION

PANELBOARDS (EXISTING): ADD CIRCUIT BREAKERS (FULL SIZED BREAKERS) AS REQUIRED FOR CIRCUITING. MATCH PRECISELY BRAND AND PROVIDE A.I.C. RATING AS INDICATED ON DRAWINGS. TANDEM AND PIGGY-BACK BREAKERS ARE NOT PERMITTE NDICATED ON BRAWINGS. TANDEM AND FIGGT-BACK BREAKERS ARE NOT PERMITTED. ALL LUGS OR CONNECTORS TO BE 60°C FOR PANEL LESS THAN OR EQUAL 100 AMPS AND 75°C RATED OF GREATER THAN 100AMPS MINIMUM. PANELBOARDS (NEW): SHALL BE RATED AS SHOWN ON DRAWINGS WITH PLATED COPPER BUSSING. PROVIDE NEMA ENCLOSURES AS REQUIRED BY CODE FOR REGULATION. BACK BOXES ENLARGED FOR DOUBLE NEUTRALS AND LUGS CAPABLE OF OVERSIZING ISOLATED GROUND AND NORMAL GROUND BUS. ALL LUGS OR CONNECTORS TO BE 60°C FOR PANEL LESS THAN OR EQUAL 100 AMPS AND 75°C RATED OF GREATER THAN 100AMPS MINIMUM. PANELBOARD CABINET SHALL BE EQUIPPED WITH

PIANO HINGES WITH DOOR IN DOOR CONSTRUCTION. CIRCUITS PROVIDE SWITCHED NEUTRALS ON ALL CIRCUIT BREAKERS FEEDING CLASS 1
AND CLASS 2 AREAS WITH NEUTRALS. GFCI ON CIRCUITS WITH NEUTRALS TO DEVICES ABOVE CLASSIFIED AREAS. ALL LIGHTING PANELS/CIRCUIT BREAKERS SHALL BE RATED FOR CONTINUOUS DUTY. HACR RATED BREAKERS SHALL BE INSTALLED FOR ALL HVAC CIRCUITS CONTAINING MULTIPLE MOTOR LOADS. ALL EQUIPMENT (PANELS, DISCONNECT SWITCHES, STARTERS, ETC.) WILL BE MARKED WITH BLACK OR RED ENGRAVERS STOCK TAGS EMBOSSED WITH 1/4" HIGH LETTERS

DESCRIBING EACH ITEM. CONDUCTORS WILL BE MARKED AT ALL TERMINATION AN

JUNCTION POINTS (PANELS, JUNCTION BOXES, SPLICES, ETC.) WITH LABELS BEARING

HE PANEL AND CIRCUIT NUMBER WHICH FEEDS EACH CONDUCTOR (PER NEC 210.4, ALL PANELBOARDS WILL HAVE TYPED DIRECTORY CARDS IDENTIFYING ALL CIRCUITS AND SPACES.
ACCEPTABLE MANUFACTURERS FOR PANELBOARDS, SWITCHBOARDS, AND

TRANSFORMERS SHALL BE PER SECTION 3.15 OF THIS SPECIFICATION. TRANSFORMERS 15 KVA AND ABOVE SHALL BE 150°C TEMPERATURE RISE ABOVE 40°C AMBIENT. ALL INSULATING MATERIALS TO BE IN ACCORDANCE WITH NEMA ST20-1972 STANDARDS FOR A 220°C UL COMPONENT RECOGNIZED INSULATION SYSTEM. SINGLE PHASE TRANSFORMERS 15 KVA THROUGH 50 KVA, AND THREE PHASE TRANSFORMERS THROUGH 45 KVA SHALL BE DESIGNED SO THEY CAN BE FITHER FLOOR OR WAL MOUNTED. THE TRANSFORMER SHALL BE LISTED BY UNDERWRITERS LABORATORY FOR SPECIFIED TEMPERATURE RISE. TRANSFORMERS 75 KVA AND ABOVE SHALL BE ESIGNED FOR FLOOR INSTALLATION ONLY UNLESS NOTED OTHERWISE. LABEL ALL PANELS/TRANSFORMERS/DISCONNECTS WITH "WARNING" - ELECTRICAL EQUIPMENT - DANGER - QUALIFIED PERSONNEL ONLY TO OPERATE ON OPEN

DISCONNECT SWITCHES WILL BE COMMERCIAL-DUTY, QUICK-MAKE, QUICK-BREAK, HORSEPOWER RATED, NEMA 1 INDOOR, NEMA 3R GASKETED, (4X) NEMA 12, OR NEMA 7 AS APPLICABLE WITH FUSES PER DRAWING.

MANUAL MOTOR STARTERS WITH THERMAL OVERLOADS WILL BE PROVIDED FOR FRACTIONAL HORSEPOWER MOTORS 1/2 HP OR GREATER. SQUARE 'D' CLASS 2510, 2511, 2512. AMBIENT COMPENSATED AS REQUIRED. MAGNETIC MOTOR STARTERS WITH THERMAL OVERLOADS, (2) AUXILIARY CONTACT SWITCHES, INTERNAL LINE VOLTAGE TO 24 VOLT TRANSFORMER (250VA, MIN) WITH

PROPER PRIMARY/SECONDARY PROTECTION, AMBIENT COMPENSATED, RED RUNNING LIGHT, HAND-OFF-AUTO, ACROSS THE LINE STARTERS. SHALL BE PROVIDED WITH ALL MOTOR SHOWN ON THE DRAWING (1 H.P. TO 25 H.P.). CONTROL PANELS CONTROL PANELS SHALL HAVE A WITHSTAND RATING OF 10,000 AMPS FOR .5 SEC. UNLESS INDICATED OTHERWISE ON THE DRAWINGS.

8.0 LIGHT FIXTURES FURNISH AND INSTALL ALL LIGHTING FIXTURES COMPLETE WITH LAMPS. WHIPS AND ACCESSORIES. ALL RECESSED FIXTURES WILL BE RATED FOR USE IN ANY CEILING APPLICATIONS AND BE THERMALLY PROTECTED. MOUNTING TYPE AND VOLTAGE OF FIXTURES IS THE RESPONSIBILITY OF THE

CONTRACTOR. (4) EARTHQUAKE CLIPS WILL BE INSTALLED ON EACH FIXTURE MOUNTED N GRID OR FLÀNGE TYPE CEILINGS. FLUORESCENT FIXTURE LENSES WILL B ACRYLIC, .125" THICK MINIMUM. ALL FIXTURES TO BE INSTALLED IN SYMMETRICAL MANNER FREE FROM LIGHT LEAKS AND DIRTY LENSES OR REFLECTORS.
ALL LAY-IN FIXTURES IN ACOUSTICAL CEILING SYSTEMS WILL BE INSTALLED PER IBC SUPPORT FIXTURES PER IBC WITH TWO LOOSE SIZE #9 WIRES STRUCTURES ON OPPOSITE CORNERS AND 2 TAUGHT SIZE #9 WIRE TO STRUCTURE AT CORNERS AND/OR FIXTURE SHALL BE FASTENED BY SCREWS INTO T-BAR RUNNERS IN

FLUORESCENT LAMPS:
51.00 OR PENDERING INDEX) MINIMUM.

8.5.3 AS NOTED ON PLANS INCANDESCENT LAMPS: 8.5.4 130V FOR ALL "A" TYPE LAMPS.

AS NOTED ON PLANS

BALLASTS ALL BALLASTS SHALL BE: HIGH POWER FACTOR, UL LISTED, CBM CERTIFIED AND ETL TESTED.

8.6.1.2 HAVE A SOUND RATING OF "A"
8.6.1.3 HAVE THD < 10%
8.6.1.4 HAVE GREATER THAN 0.9 POWER FACTOR FLUORESCENT BALLAST SHALL:
6.2.1 START RELIABLY DOWN TO AT LEAST 60°F (0°F WHEN INDICATED AS LOW TEMPERATURE ON THE DRAWINGS OR IN AN OPEN WAREHOUSE OR 8.6.2.2 BE RATED FOR AN AMBIENT OF AT LEAST 140°F.

HID BALLASTS SHALL: 3.1 START RELIABLY DOWN TO AT LEAST — 20°F B.6.3.2 BE RATED FOR AN AMBIENT OF AT LEAST 131°F

B.6.3.3 BE POTTED AND ENCASED WHEN INSTALLED IN AN OFFICE 3.6.3.4 HAVE PULSE START TECHNOLOGY. ELECTRONIC DIMMING BALLAST SHALL

8.6.4.1 WITHSTAND SURGES AS SPECIFIED IN ANSI C62.41
8.6.4.2 PREHEAT LAMP CATHODES BEFORE APPLYING ARC VOLTAGE
8.6.4.3 INTERNALLY LIMIT INRUSH CURRENT TO NOT EXCEED THREE AMPS AT 8.6.4.4 BE UL LISTED AND CLASS P THERMALLY PROTECTED BE INAUDIBLE IN A 27Db AMBIENT THROUGHOUT THE DIMMING RANGE. HAVE A DIMMING RANGE FROM 100% TO 10% ILLUMINANCE LEVEL.

8.6.4.7 ACCEPTABLE MANUFACTURERS: ADVANCE, MOTOROLA, LUTRON, 8.7.1 ALL DEVICES SHALL BE UL LISTED SPECIFICALLY FOR THE REQUIRED LOADS I.E., INCANDESCENT, FLUORESCENT, L.E.D., LOW VOLTAGE, ELECTRONIC LOW VOLTAGE).

DIMMERS AND SWITCHES SHALL MEET OR EXCEED ANSI/IEEE STD.C62.41-1980 DIMMERS AND SWITCHES SHALL MEET UL 20 AND UL 1472. DIMMER CONTROL SHALL BE LINEAR SLIDE. DIMMER SHALL PROVIDE A SMOOTH AND CONTINUOUS SQUARE LAW DIMMING CURVE.

8.7.5 DIMMERS SHALL UTILIZE AN LC FILTERING NETWORK TO MINIMIZE INTERFERENCE WITH PROPERLY INSTALLED RADIO, AUDIO, AND VIDEO EQUIPMENT. DIMMER CONTROL SLIDER SHALL BE CAPTURED.

FACEPLATE SHALL SNAP ON TO DEVICE WITH NO VISIBLE MEANS OF

ACCEPTABLE MANUFACTURES FOR DIMMERS ARE LUTRON, LITHONIA, LEVITON

3.7.9 ALL DIMMERS WITH L.E.D.'S SHALL BE RATED/LISTED FOR USE WITH THE LIGHTING CONTACTORS SHALL HAVE A WITHSTAND RATING OF 14,000 AMPS FOR 0.5 SECONDS UNLESS INDICATED OTHERWISE ON THE DRAWINGS.

LIGHTING CONTROL PANELS 8.9.1 PROGRAMMING SHALL BE COORDINATED WITH OWNER AND TENANT PRIOR TO 8.9.2 ALL PROGRAMMING SHALL MEET MINIMUM REQUIREMENTS OF ADOPTED NTERNATIONAL ENERGY CONSERVATION CODE (IECC) 8.9.3 ALL RELAYS SHALL BE RATED FOR MINIMUM OF 14,000 A.I.C.

AND PRESCOLITE, LIGHTOLIER OR PRIOR APPROVED EQUAL.

PROVIDE AND INSTALL A COMPLETE SYSTEM OF EMPTY RACEWAYS 3/4" EMT MINIMUM WITH PULL STRAP/CORD. PROVIDE REQUIRED/REQUESTED INFORMATION TO TELEPHONE 10.0 DATA/INFORMATION SYSTEM

PROVIDE AND INSTALL A COMPLETE SYSTEM OF RACEWAYS (CABLE TRAYS, J-HOOKS, CONDUIT SLEEVES) OF PREFERABLY OPEN CONSTRUCTION WITH PULL LINE. RACEWAYS

9.0 TELEPHONE SYSTEM

ATTACHMENT

HIS SECTION SHOWN FOR REFERENCE ONLY. FIRE ALARM DESIGN TO BE PROVIDED AS A DEFERRED SUBMITTAL BY OTHERS, FIRE ALARM CONTRACTOR SHALL PROVID VINGS AND DESIGN CALCULATIONS STAMPED AND SIGNED BY A PROFESSIONAL

PROVIDE AND INSTALL A COMPLETE AND WORKING CLASS "B" FIRE ALARM SYSTEM OR AS INDICATED BY THE FIRE ALARM ONE—LINE DIAGRAM ON THE DRAWINGS. POWER LIMITED BY N.E.C. DEFINITION. ALL WIRING WITH DEVICES AND CONDUCTORS TO BE U.L., F.M., OR C.S.A. LISTED AND APPROVED (LABELS ON EQUIPMENT).

11.1.1 AS PROVIDED BY DRAWINGS ALL SPRINKLER SYSTEMS WITH GREATER THAN 100 HEADS SHALL HAVE MINIMUM 6 ZONE CLASS B FIRE ALARM CONTROL PANEL WITH AUTO DIALER. SPRINKLER SYSTEMS WITH LESS THAN 100 HEADS REQUIRE ONLY CONNECTION TO WATER FLOW AND TAMPER SWITCH AND MAY BE INDICATED ON

IECC: 2018

DESIGN CODES

DESIGNER/ENGINEER PRIOR TO ANY DEVIATION

FROM THIS SET OF ELECTRICAL DESIGN PLANS

ANY CHANGES TO THE DESIGN, IF APPROVED

BY ENGINEER, WILL REQUIRE REVISIONS TO

PLANS AND POSSIBLE ADDITIONAL SERVICE

ELECTRICAL CONTRACTOR SHALL NOTIFY

NEC: 2017

DRAWINGS IN SOME CASES. ALL WIRING TO BE #14 A.W.G. CU., STRANDED, 105° INSULATED, PLENUM RATED. INSTALLED 600V. RATED INSULATION IN CONDUIT OR RACEWAY WITH SIX (6) FEET SPACING BETWEEN OUTPUT/INPUT PER N.F.P.A.

SYSTEM INSTALLATION AND DEVICES WILL BE IN ACCORDANCE WITH ALL PERTINENT AND MOST STRINGENT REQUIREMENTS (ONLY POWER LIMITED SYSTEMS WILL BE 11.3.1.1 70 - NATIONAL ELECTRICAL CODE 11.3.1.2 72 A,B,C,D,E,F,G,H (LOCAL SIGNALING SYSTEMS (A), AUTOMATIC FIRE DETECTION (E), ALARM SIGNALING APPLIANCES (G), ETC.) 11.3.1.3 71 — CENTRAL STATION SIGNALING

UPDATED: 09-09-2014

AMERICANS WITH DISABILITIES ACT (ADA) AND THE ARIZONA HANDICAP 11.3.4 I.C.B.O. – INTERNATIONAL BUILDING CODE & INTERNATIONAL FIRE CODE AND ANY STATE OR LOCAL CODES WHICH MAY BE APPLICABLE.

11.3.5 WORK SHALL BE COMPLETED BY UL CERTIFIED INSTALLERS. DO NOT POSITION SMOKE DETECTORS WITHIN 36" OF ANY AIR HANDLING GRILLES (SUPPLY OR RETURN) OR WITHIN 12" OF FACILITY LIGHTING FIXTURES ALL DEVICE BACK BOXES TO BE MOUNTED FLUSH, PERPENDICULAR TO FINISH WALLS AND CEILING SURFACES USING STANDARD "TRADE" MOUNTING HARDWARE.
CONTRACTOR WILL COMPLY WITH PROJECT SPECIFICATIONS, AND SUPPLY SHOP
DRAWINGS, CUTS, SAMPLES, ETC. TO THE ENGINEER WITHIN 5 DAYS OF CONTRACT.

ARS TITLE 26, CHAPTER 2-3 (ARIZONA STATE FIRE CODE)

11.8EXTEND EXISTING SYSTEM TO NEW DEVICES. LOADS ON EACH ZONE. OR RUN TO BE CALCULATED (RESULTS TO ENGINEER) PRIOR TO INSTALLATION, ADDITIONAL RUNS, ZONES, CONTROL CARDS, ETC., REQUIRED FOR FACP/FAAP TO BE INCLUDED IN BID.

11.9 EDWARDS, SIMPLEX, FIRELITE OR PYROTRONICS ARE ACCEPTABLE MANUFACTURERS.
INSTALLATION SHOULD BE COMPATIBLE TO THE MAXIMUM EXTENT PRACTICAL WITH FUTURE
ADDITIONS OF EQUIPMENT AND DEVICES TO INCLUDE OTHER MANUFACTURERS. 11.10 ALL PENETRATIONS OF FIRE RATED FLOORS OR WALLS SHALL BE PROTECTED BY MATERIALS AND INSTALLATION THAT CONFORM TO U.L. LISTINGS FOR THROUGH PENETRATION FIRE STOP SYSTEMS PER IBC.

11.7SYSTEM MONITORED AT ACM, U.L. APPROVED REMOTE MONITORING STATION LOCATED IN

12.0 ELEVATORS

ALL INSTALLATIONS AND EQUIPMENT SHALL COMPLY WITH N.E.C. ARTICLE "ELEVATORS" AND ASME/ANSI STANDARDS A17.1. SPECIFIC REQUIREMENTS INCLUDE BUT ARE NOT LIMITED TO: 12.2.1 A SEPARATE BRANCH CIRCUIT WITH DISCONNECT (CAPABLE OF BEING LOCKED IN THE OPEN POSITION, LOCATED IN THE MACHINE ROOM) (BRADY NO. 2AF98 OR EQUAL.) PROVIDED FOR EACH ELEVATOR CAR FOR LIGHTS, FANS AND/OR ACCESSORIES.
12.2.2 HVAC SYSTEMS SHALL BE PROVIDED WITH SEPARATE BRANCH CIRCUIT. CAPABLE OF BEING LOCKED IN THE OPEN POSITION LOCATED IN THE MACHINE ROOM) (BRADY NO 24F98 OR FOLIAL) (LE NO HVAC TAPS WITH OTHER LINITS) GECL PROTECTED OUTLET (REQUIRED) 2.2.4 DEDICATED BRANCH CIRCUITS FOR HOISTWAY PIT LIGHTING AND GFCI OUTLET (REQUIRED). MINIMUM LIGHTING SHALL BE 4'-0" FLUORESCENT STRIP, (2) OUTLET (REQUIRED). MINIMON EIGHTING STATE
LAMPS AND WRE GUARD.

12.2.5 NO CONDUITS, PIPES, DUCTS OR OTHER RACEWAY SYSTEMS SHALL
PASS INTO OR THROUGH THE ELEVATOR EQUIPMENT ROOM OR HOISTWAY WHICH IS NOT DIRECTLY RELATED TO ELEVATOR OPERATION. (THIS DOES NOT INCLUDE REQUIRED SPRINKLER PIPING).

12.2.6 IF SPRINKLERS ARE PRESENT. IN EITHER OR BOTH ELEVATOR EQUIPMENT ROOM AND ELEVATOR HOISTWAY, THE CONTRACTOR SHALL PROVIDE A SHUNT TRIP MECHANISM AS A MEANS OF DISCONNECTING POWER TO THE AFFECTED ELEVATOR AND CONTROLLER PRIOR TO THE APPLICATION OF WATER. (SPRINKLER ACTIVATION OUTSIDE OF ELEVATOR EQUIPMENT ROOM OR HOISTWAY SHALL NOT DISCONNECT POWER).

12.2.7 INSTALL 165' RATE OF RISE HEAT DETECTORS IN THE ELEVATOR EQUIPMENT ROOM, TOP OF HOIST WAY AND BOTTOM OF HOISTWAY — ALL WITH AUX. CONTACTS FOR CONNECTION TO BOTH FIRE ALARM CONTROL PANEL AND SHUNT TRIP MECHANISM IN EQUIPMENT ROOM. ANY DETECTOR ACTIVATION WILL SHUNT TRIP THE EQUIPMENT.

12.2.8 INSTALL SMOKE DETECTORS IN ELEVATOR EQUIPMENT ROOM, TOP OF HOISTWAY AND BOTTOM OF HOISTWAY AND CONNECT TO FIRE ALARM CONTROL PANEL AS A MEANS OF PRELIMINARY SHUT DOWN WARNING, AND TO ELEVATOR

CONTROLLER FOR RECALL FUNCTION.

12.2.9 PROVIDE SMOKE DETECTORS IN ALL ELEVATOR LOBBIES. PROVIDE

AUXILIARY CONTACTS AT EACH SMOKE DETECTOR FOR CONNECTION TO FLEVATOR

CONTROLLER FOR ALTERNATE FLOOR RECALL MODE DURING A FIRE. 13.0 SURGE PROTECTIVE DEVICES (SPD) THE SPD UNIT SHALL BE DESIGNED, MANUFACTURED & TESTED IN ACCORDANCE WITH:

13.10.1 EATON/CUTLER HAMMER

UL 1449 3RD EDITION & 1283 CSA CERTIFIED CSA 22.2 13.1.3 ANSI/IEEE C62.41
SPD UNIT SHALL BE INSTALLED PER NEC SECTION 285
FOR EXTERNALLY MOUNTED SPD UNITS, FIELD WRING SHALL BE TWISTED NEATLY AND ROUTED TO MINIMIZE LENGTH.

SUBMIT SHOP DRAWINGS & PRODUCT INFORMATION FOR EACH SPD USED INCLUDING: VERIFICATION OF COMPLIANCE TO STANDARDS

13.4.2 UNIT SHORT CIRCUIT CURRENT RATING (SCCR) VOLTAGE PROTECTION RATINGS (VPR) FOR ALL MODES 13.4.4 MAXIMUM CONTINUOUS OPERATING VOLTAGE RATING (MCOV)
13.4.5 MINIMUM 5 YEAR WARRANTY FROM DATE OF INSTALLATION QUALITY: SPD MANUFACUTER SHALL BE ISO 9001 OR 9002 CERTIFIED

MAXIMUM CONTINUOUS OPERATING VOLTAGE (MCOV) SHALL BE GREATER THAN 125% OF THE NOMINAL SYSTEM OPERATING VOLTAĞE SPD SHALL BE FACTORY INSTALLED (INTERNALLY) UNLESS SPECIFIED OTHERWISE. SPD SPECIFICATIONS:

13.8.1 OPERATING VOLTAGE TO MATCH SYSTEM AT POINT OF CONNECTION MINIMUM 20KA I-NOMINAL (L-N)
MINIMUM 200KA SCCR RATING PER PHASE MINIMUM 7 MODE PROTECTION UNLESS SPECIFIED OTHERWISE
VISUAL DIAGNOSTICS INCLUDING A MINIMUM OF ONE LED TO INDICATE SPD


SPD SHALL HAVE RESPONSE TIME OF NO GREATER THAN 1/2 NANOSECOND 13.8.7 NEMA 3/3R ENCLOSURE WHERE INSTALLED OUTDOORS SPD SHALL INCORPORATE A UL 1283 LISTED EMI/RFI FILTER ACCEPTABLE MANUFACTURERS:















SHEET NUMBER

ELECTRICAL


SYMBOLS & SPECS


Project # 21482 1140 WEST HARWELL ROAD GILBERT, ARIZONA 85233



NOT FOR CONSTRUCTION

IF DRAWING IS NOT PLOTTED AT 24 X 36 THEY ARE NOT FULL SIZE





PRE-CURFEW DESIGN HOURS SHALL BE DEFINED FROM NOT LATER THAN

ONE HOUR AFTER BUSINESS CLOSING AND POST-CURFEW DESIGN HOURS

SHALL BE DEFINED AS NOT EARLIER THAN ONE HOUR BEFORE BUSINESS

OPENING. ALL EXTERIOR LIGHTS SHALL BE DIMMED BY 60% DURING POST-CURFEW TO COMPLY WITH IECC 2018 C405.2.6. EXTERIOR LIGHTING

CONTROLS.

PROJECT NUMBER 21023.00

CHECKED BY 1*=20'-0* SHEET NAME

ELECTRICAL SITE

LIGHTING PLAN

SHEET NUMBER

1140 WEST HARWELL ROAD GILBERT, ARIZONA 85233 Рн. 480.813.9000 F.w. 480.813.9001 EMAIL email@hawkinsdg.com

All concepts, designs and data indicated on these drawings are the sole property of the Hawkins Design Group Inc., and shall not be used for any other purpose other than originally intended without written permission of the engineer.


IF DRAWING IS NOT PLOTTED AT 24 X 36 THEY ARE NOT FULL SIZE


DESIGNER/ENGINEER PRIOR TO ANY DEVIATION FROM THIS SET OF ELECTRICAL DESIGN PLANS.

ANY CHANGES TO THE DESIGN, IF APPROVED

BY ENGINEER, WILL REQUIRE REVISIONS TO PLANS AND POSSIBLE ADDITIONAL SERVICE








Luminaire Schedule									
Tag	Symbol	Qty	[MANUFAC]	Label	Arrangement	LLF	Luminaire	Luminaire	
							Lumens	Watts	
SA		20	U.S. ARCHITECTURAL LIGHTING	LUM-PLED-IV-FT-80LED-700mA-NW	Single	0.920	20452	173.6	

Calculation Summary							
Label	CalcType	Units	Avg	Max	Min	Avg/Min	Max/Min
Object_1_Planar	Illuminance	FC	3.80	8.3	0.4	9.50	20.75

PRE-CURFEW DESIGN HOURS SHALL BE DEFINED FROM NOT LATER THAN ONE HOUR AFTER BUSINESS CLOSING AND POST-CURFEW DESIGN HOURS SHALL BE DEFINED AS NOT EARLIER THAN ONE HOUR BEFORE BUSINESS OPENING. ALL EXTERIOR LIGHTS SHALL BE DIMMED BY 60% DURING POST-CURFEW TO COMPLY WITH IECC 2018 C405.2.6. EXTERIOR LIGHTING CONTROLS.


DESIGN CODES IECC: 2018 NEC: 2017

ELECTRICAL CONTRACTOR SHALL NOTIFY DESIGNER/ENGINEER PRIOR TO ANY DEVIATION FROM THIS SET OF ELECTRICAL DESIGN PLANS ANY CHANGES TO THE DESIGN, IF APPROVED BY ENGINEER, WILL REQUIRE REVISIONS TO PLANS AND POSSIBLE ADDITIONAL SERVICE



IF DRAWING IS NOT PLOTTED AT 24 X 36 THEY ARE NOT FULL SIZE





DR-2

11.09.21

21023.00

ELECTRICAL


PHOTOMETRICS

PRE-CURFEW

1*=20'-0*







Luminaire Schedule								
Tag	Symbol	Qty	[MANUFAC]	Label	Arrangement	LLF	Luminaire Lumens	Luminaire Watts
SA		20		LUM-PLED-IV-FT-80LED-700mA-NW	SINGLE	0.650	20452	173.6


Calculation Summary							
Label	CalcType	Units	Avg	Max	Min	Avg/Min	Max/Min
Object 1 Planar	Illuminance	FC	2.67	5.8	0.3	8.90	19.33

PRE-CURFEW DESIGN HOURS SHALL BE DEFINED FROM NOT LATER THAN ONE HOUR AFTER BUSINESS CLOSING AND POST-CURFEW DESIGN HOURS SHALL BE DEFINED AS NOT EARLIER THAN ONE HOUR BEFORE BUSINESS OPENING. ALL EXTERIOR LIGHTS SHALL BE DIMMED BY 60% DURING POST—CURFEW TO COMPLY WITH IECC 2018 C405.2.6. EXTERIOR LIGHTING

NOT FOR CONSTRUCTION


DESIGN CODES IECC: 2018 NEC: 2017

ELECTRICAL CONTRACTOR SHALL NOTIFY DESIGNER/ENGINEER PRIOR TO ANY DEVIATION FROM THIS SET OF ELECTRICAL DESIGN PLANS ANY CHANGES TO THE DESIGN, IF APPROVED BY ENGINEER, WILL REQUIRE REVISIONS TO PLANS AND POSSIBLE ADDITIONAL SERVICE



PRELIMINARY

IF DRAWING IS NOT PLOTTED AT 24 X 36 THEY ARE NOT FULL SIZE



DR-3

11.09.21


21023.00

ELECTRICAL

PHOTOMETRICS

POST-CURFEW

1*=20'-0*



U.S. Architectural Lighting

660 West Avenue O, Palmdale, CA 93551
Phone (661) 233-2000 Fax (661) 233-2001
www.usoflg.com

PRELIMINARY NOT FOR CONSTRUCTION

U.S. ARCHITECTURAL

NEC₁ 2017

DESIGN CODES

ELECTRICAL CONTRACTOR SHALL NOTIFY

ANY CHANGES TO THE DESIGN, IF APPROVED BY ENGINEER, WILL REQUIRE REVISIONS TO PLANS AND POSSIBLE ADDITIONAL SERVICE

IECC: 2018

Project # 21482 DESIGNER/ENGINEER PRIOR TO ANY DEVIATION FROM THIS SET OF ELECTRICAL DESIGN PLANS

IF DRAWING IS NOT PLOTTED AT 24 X 36 THEY ARE NOT FULL SIZE

Project Contact/Designer: CHAD CURRY HAWKINS DESIGN GROUP NC. ELECTRICAL CONSULTING ENGINEERS 1140 WEST HARWELL ROAD GILBERT, ARIZONA 85233 Рн. 480.813.9000 Fax. 480.813.9001 Емац. email@hawkinsdg.com All concepts, designs and data indicated on these drawings are the sole property of the Hawkins Design Group Inc., and shall not be used for any other purpose other than originally intended without written permission of the engineer.

SHEET NUMBER

ELECTRICAL

PHOTOMETRICS

POST-CURFEW

PROJECT NUMBER 21023.00

11.09.21

SHEET NAME

AG

1*=20'-0*

Expires: XX/XX/XX

EXPANSION FOR

BUILDING