HARRY & CARDY LAKE 928 SEO EST MESA AZ \$5208 ROOFING TYPE SPECIFIED: 15 LB. VAPOR BARRIER ON 1/2" O.S.B. ROOF SHEATHING -TRUSSES 2x4 WOOD RAFTER AT 24" O.C. METAL TIES AT RAFTER -DOUBLE TOP PLATE-FASCIA TO MATCH EXIST. -0 2x4 WOOD STUDS AT 16" O.C. WITH-1/2" O.S.B. SHEATHING AND STUCCO FINISH PRESSURE TREATED BOARD IN CONTACT 0 W/ CONC. WALL. ANCHOR WITH 1/2" DIA. BOLTS AT 48" O.C. MAX. GROUT SOLID CONTINUOUS CONCRETE FOOTING W/ -(1) #4 AT BOTTOM 1'-0" GARAGE WALL PUT DIMENSIONS AT THE CIRCLES PROPERTY ADDRESS= CITY OF MESA - FOR REFERENCE ONLY - EXAMPLE

128 5 80th St 1928 5 80th St 10250 AZ 85208 0 EXISTING ROOF CONSTRUCTION TO REMAIN. ADD 1/2" GYPSUM BOARD TO UNDERSIDE OF EXISTING RAFTERS. 15 = Fielt 30 Year Acr ShingLes EXISTING POST AND BEAM TO REMAIN IN PLACE. 1/2" BETWEEN BEAM AND WALL PLATE INFILL BETWEEN POSTS WITH WALL-CONSTRUCTION THAT IS 2x 4 AT 10" O.C. WITH 1/2" GYPSUM BOARD ON INSIDE FACÉ. EXTERIOR FINISH = T 1-11 0 Sidiny 2 x 4 PRESSURE TREATED PLATE PLATE ANCHORS AT 32" O.C. WITH A MINIMUM 1 1/8" EMBED INTO CONCRETE, 12" MAX FROM CORNERS, SPLICES AND OPENINGS, MIN. 3 PER PLATE -**GRADE** EXISTING SLAB -EXTEND EXTERIOR FINISH 3/4" MIN. BELOW BOTTOM OF PLATE. APPLY SEALANT. **ENCLOSURE** PUT DIMENSIONS AT THE CIRCLES PROPERTY ADDRESS= ALL METAL CONNECTORS SHALL BE ICC LISTED AND INSTALLED PER MANUFACTURER'S INSTRUCTIONS CITY OF MESA - FOR REFERENCE ONLY - EXAMPLE

