LITHONIA LIGHTING®

Catalog Number

Notes

Type

FEATURES & SPECIFICATIONS

INTENDED USE — Typical applications include corridors, lobbies, conference rooms and private offices.

CONSTRUCTION — Galvanized steel mounting/plaster frame; galvanized steel junction box with bottom-hinged access covers and spring latches. Reflectors are retained by torsion springs.
Vertically adjustable mounting brackets with commercial bar hangers provide 3-3/4" total adjustment.
Two combination ½"-3/4" and four ½" knockouts for straight-through conduit runs. Capacity: 8 (4 in, 4 out). No. 12 AWG conductors, rated for 90°C.
Accommodates 12"–24" joist spacing.
Passive cooling/thermal management for 25°C standard; high ambient (40°C) option available. Light engine and drivers are accessible from above or below ceiling.
Max ceiling thickness 1-1/2".

OPTICS — LEDs are binned to a 3-step SDCM; 80 CRI minimum. 90 CRI optional.
LED light source concealed with diffusing optical lens.
General illumination lighting with 1.0 S/MH and 55° cutoff to source and source image.
Self-flanged anodized reflectors in specular, semi-specular, or matte diffuse finishes. Also available in white and black painted reflectors.

ELECTRICAL — Multi-volt (120-277V, 50/60Hz) 0-10V dimming drivers mounted to junction box, 10% or 1% minimum dimming level available.
0-10V dimming fixture requires two (2) additional low-voltage wires to be pulled.
70% lumen maintenance at 60,000 hours.

LISTINGS — Certified to US and Canadian safety standards. Wet location standard (covered ceiling). IP55 rated. ENERGY STAR® certified product.

BUY AMERICAN — Product with the BAA option is assembled in the USA and meets the Buy America(n) government procurement requirements under FAR, DFARS and DOT. Please refer to www.acuitybrands.com/buy-american for additional information.

WARRANTY — 5-year limited warranty. Complete warranty terms located at: www.acuitybrands.com/support/warranty/terms-and-conditions

Note: Actual performance may differ as a result of end-user environment and application.
All values are design or typical values, measured under laboratory conditions at 25°C.
Specifications subject to change without notice.

A+ Capable options indicated by this color background.

LDN6

6" Open and WallWash LED
Non-IC
New Construction Downlight

Buy American

ORDERING INFORMATION

Lead times will vary depending on options selected. Consult with your sales representative.

Example: LDN6 35/15 L0GAR LSS MVOLT EZ10

LDN6													
Series		**Color temperature**		**Lumens**[1]			**Aperture/Trim Color**			**Finish**		**Voltage**	
LDN6 6" round		27/	2700K	05	500 lumens	25	2500 lumens	L06	Downlight	AR	Clear	LSS	Semi-specular	MVOLT	Multi-volt
		30/	3000K	07	750 lumens	30	3000 lumens	LW6	Wallwash	WR[1]	White	LD	Matte diffuse	120	120V
		35/	3500K	10	1000 lumens	40	4000 lumens			BR[1]	Black	LS	Specular	277	277V
		40/	4000K	15	1500 lumens	50	5000 lumens							347[1]	347V
		50/	5000K	20	2000 lumens										

Driver		**Options**			
GZ10	0-10V driver dims to 10%	SF[4]	Single fuse	NBO[4]	nLight® Lumen Compensation
GZ1	0-10V driver dims to 1%	STWH[1]	White painted flange	JOT[11]	Wireless room control with "Just One Touch" pairing
D10	Minimum dimming 10% driver for use with JOT	TBBL[1]	Black painted flange	NPS80EZ[7]	nLight® dimming pack controls 0-10V eldoLED drivers (EZ10, EZ1).
D1	Minimum dimming 1% driver for use with JOT	EL[4]	Emergency battery pack with integral test switch. 10W Constant Power, Not Certified in CA Title 20 MAEDBS	NPS80EZER[7]	nLight® dimming pack controls 0-10V eldoLED drivers (EZ10, EZ1). ER controls fixtures on emergency circuit.
EZ10	0-10V eldoLED driver with smooth and flicker-free deep dimming performance down to 10%	ELR[4]	Emergency battery pack with remote test switch. 10W Constant Power, Not Certified in CA Title 20 MAEDBS	HAO[12]	High ambient option
EZ1	0-1V eldoLED driver with smooth and flicker-free deep dimming performance down to 1%	ELSD[4]	Emergency battery pack with self-diagnostics, integral test switch. 10W Constant Power, Not Certified in CA Title 20 MAEDBS	CP[13]	Chicago Plenum
EDA8	eldoLED DALI SOLDRIVE dim to dark	ELRSD[4]	Emergency battery pack with self-diagnostics, remote test switch. 10W Constant Power, Not Certified in CA Title 20 MAEDBS	RRL___	RELOC®-ready luminaire connectors enable a simple and consistent factory installed option across all ABL luminaire brands. Available only in RRLA, RRLB, RRLAE, and RRLC125. Refer to RRL spec sheet on www.acuitybrands.com for the RELOC product specification options.
		E10WCP[4]	Emergency battery pack. 10W Constant Power with integral test switch. Certified in CA Title 20 MAEDB	NLTAIR2[9, 10]	nLight® Air enabled
		E10WCPR[4]	Emergency battery pack, 10W Constant Power with remote test switch. Certified in CA Title 20 MAEDB	NLTAIRER2[9, 10]	nLight® AIR Dimming Pack Wireless Controls. Controls fixtures on emergency circuit, not available with battery pack options
		NPP16D[7]	nLight® network power/relay pack with 0-10V dimming for non-eldoLED drivers (GZ10, GZ1).	NLTAIREM2[9,10]	nLight® AIR Dimming Pack Wireless Controls. UL924 Emergency Operation, via power interrupt detection. Available with battery pack options.
		NPP16DER[7]	nLight® network power/relay pack with 0-10V dimming for non-eldoLED drivers (GZ10, GZ1). ER controls fixtures on emergency circuit.	BAA	Buy America(n) Act Compliant
				90CRI	High CRI (90+)

Accessories: *Order as separate catalog number.*	
PS1055CP	FMC Power Sentry batterypack, T20 compliant, field installable, 10w constant power
EAC ISSM 375	Compact interruptible emergency AC power system
EAC ISSM 125	Compact interruptible emergency AC power system
GRA6B JZ	Oversized trim ring with 8" outside diameter [1]

Notes
1 Overall height varies based on lumen package; refer to dimensional chart on page 3.
2 Not available with finishes.
3 Not available with emergency options.
4 Must specify voltage 120V or 277V.
5 Available with clear (AR) reflector only.
6 12.5" of plenum depth or top access required for battery pack maintenance.
7 Specify voltage. ER for use with generator supply EM power. Will require an emergency hot feed and normal hot feed.
8 Fixture begins at 80% light level. Must be specified with NPS80EZ or NPS80EZER. Only available with EZ10 and EZ1 drivers.
9 Not available with CP, NPS80EZ, NPS80EZER, NPP16D, NPP-16DER or NBO options.
10 NLTAIR2, NLTAIRER2 and NLTAIREM2 not recommended for metal ceiling installations.
11 Fixture height is 6.5" for all lumen packages with HAO.
12 Must specify voltage for 3000lm and above. 5000lm with marked spacing 24 L x 24 W x 14 H. Not available with emergency battery pack option.
13 Must specify 3150 or 5K driver. Not available with nLight options. Not available with CP. Not recommended for metal ceiling installation. Not for use with emergency backup power systems other than battery packs.

D-Series Size 0
LED Area Luminaire

Buy American

Catalog Number

Notes

Type

Hit the Tab key or mouse over the page to see all interactive elements.

Specifications

EPA: 0.95 ft2 (.088 m2)
Length: 26" (66.0 cm)
Width: 13" (33.0 cm)
Height1: 3" (7.62 cm)
Height2: 7" (17.8 cm)
Weight (max): 16 lbs (7.25 kg)



Introduction

The modern styling of the D-Series is striking yet unobtrusive - making a bold, progressive statement even as it blends seamlessly with its environment. The D-Series illustrates the benefits of the latest in LED technology into a high performance, high efficacy, long-life luminaire.

The outstanding photometric performance results in sites with excellent uniformity, greater pole spacing and lower power density. It is ideal for replacing up to 400W metal halide with typical energy savings of 70% and expected service life of over 100,000 hours.

EXAMPLE: DSX0 LED P6 40K T3M MVOLT SPA NLTAIR2 PIRHN DDBXD

DSX0 LED

DSX0 LED

Forward optics		30K 3000 K	T1S Type I short (Automotive)	T5W Type V short 3	MVOLT (120V-277V) 5,6
P1	P5	40K 4000 K	T2S Type II short	T5M Type V medium	XVOLT (277V-480V) 7,8,9
P2	P6	50K 5000 K	T2M Type II medium	T5W Type V wide 3	120 9
P3	P7 1		T3S Type III short	BLC Backlight control 4	208 6
P4 1			T3M Type III medium	LCCO Left corner cutoff 4	240 6
Rotated optics			T4M Type IV medium	RCCO Right corner cutoff 4	277 6
P10 2	P12 2		TFTM Forward throw medium		347 6
P11 2	P13 1,2		T5VS Type V very short 3		480 6

Shipped included	
SPA	Square pole mounting
RPA	Round pole mounting 10
WBA	Wall bracket 3
SPUMBA	Square pole universal mounting adapter 11
RPUMBA	Round pole universal mounting adapter 11
Shipped separately	
KMA8 DDBXD	U Mast arm mounting bracket adaptor (specify finish) 12

Shipped installed	
NLTAIR2	nLight AIR generation 2 enabled 13,14
PIRHN	Network, high/low motion/ambient sensor 15
PER	NEMA twist-lock receptacle only (control ordered separately) 16
PER5	Five-pin receptacle only (control ordered separately) 16,17
PER7	Seven-pin receptacle only (leads exit fixture) (control ordered separately) 16,17
DMG	0-10V dimming extend out back of housing for external control (control ordered separately) 18

PIR	High/low, motion/ambient sensor, 8-15' mounting height, ambient sensor enabled at 5fc 19,20
PIRH	High/low, motion/ambient sensor, 15-30' mounting height, ambient sensor enabled at 5fc 19,20
PIR1FC3V	High/low, motion/ambient sensor, 8-15' mounting height, ambient sensor enabled at 1fc 19,20
PIRH1FC3V	High/low, motion/ambient sensor, 15-30' mounting height, ambient sensor enabled at 1fc 19,20
FAO	Field adjustable output 21

Shipped installed	
SF	Single fuse (120, 277, 347V) 22
DF	Double fuse (208, 240, 480V) 22
DDBXD	Dark bronze
DBLXD	Black
DNAXD	Natural aluminum
DWHXD	White
DSSXD	Sandstone
DDBTXD	Textured dark bronze
DBLBXD	Textured black
DNATXD	Textured natural aluminum
DWHGXD	Textured white
DSSTXD	Textured sandstone

Finish
DDBXD Dark bronze
DBLXD Black
DNAXD Natural aluminum
DWHXD White
DDBTXD Textured dark bronze
DBLBXD Textured black
DNATXD Textured natural aluminum
DWHGXD Textured white

NOTES
1 Not available with P4, P7, and P13.
2 P10, P11, P12 and P13 and rotated options (L90 or R90) only available together.
3 Any Type 5 distribution with photocell, is not available with WBA.
4 Not available with HS or DDL.
5 MVOLT driver operates on any line voltage from 120-277V (50/60 Hz).
6 Single fuse (SF) requires 120V, 277V or 347V. Double fuse (DF) requires 208V, 240V or 480V. XVOLT not available with fusing (SF or DF).
7 XVOLT only suitable for use with P4, P7 and P13.
8 XVOLT operates with any voltage between 277V and 480V.
9 XVOLT not available with PIR, PIRH, PIR1FC3V, PIRH1FC3V, PIRHN or PIRHN1FC3V.
10 Suitable for mounting to round poles between 3.5" and 12" diameter.
11 Universal mounting brackets intended for retrofit on existing pre-drilled poles only. 1.5 G vibration load rating per ANCI C136.31. Only usable when pole's drill pattern is NOT Lithonia template #8.
12 Must order fixture with SPA mounting. Must be ordered as a separate accessory; see Accessories information. For use with 2-3/8" diameter mast arm (not included).
13 Must be ordered with PIRHN.
14 Must be ordered with NLTAIR2. Not available with dark bronze, black, white and natural aluminum colors.
15 Must be ordered with NLTAIR2. For more information on nLight Air 2 visit this link
16 Photocell ordered and shipped as a separate line item from Acuity Brands Controls. See accessories. Shorting Cap included.
17 If RDAM8 node required, it must be ordered and shipped as a separate line item from Acuity Brands Controls. Shorting Cap included.
18 DMG not available with PIRHN, PER5, PER7, PIR, PIRH, PIR1FC3V or PIRH1FC3V. FAO.
19 Reference Controls Options table on page 4
20 Reference Motion Sensor Default Table on page 4 to see functionality.
21 Not available with SPUMBA or RPUMBA options.
22 Not available with BLC, LCCO and RCCO distribution.
23 Must be ordered with fixture for factory pre-drilling.
24 Requires luminaire to be specified with PER, PER5 or PER7 option. See Controls Table on page 4.
25 For retrofit wall/poly. Only usable when pole's drill pattern is NOT Lithonia template #8

Link to nLight Air 2

© 2011-2021 Acuity Brands Lighting, Inc. All rights reserved.

AQUA 400 ROUND LX SCONCE

ALW

PROJECT

Job _____

Type _____

Part # _____

Notes

SPECIFICATIONS

Source Xicato XTM LED module - up to 4000 source lumens
CCT 2700K, 3000K, 3500K or 4000K
Color Consistency 1x2 SDCM (MacAdam) along BBL, CCT +/- 40K to 70K, Duv +/- .001
CRI (Ra) 83 or 98
Driver / Location Integral / premium drivers must be remote mounted
Dimming 0-10V or phase to 10% standard; Ecosystem, DALI, DMX and 1% available
Input Voltage 100 to 277VAC (347VAC consult factory), phase dimmable versions are 120VAC only
Power Up to 60 watts max, depending on LED module / driver
Reflector 8°, 13°, 20°, 40°, 60°, 83° & optical accesories
Materials Tamper resistant design, stainless steel hardware, metal reflectors
Finish Powder coat - Exterior grade TGIC polyester, optional marine-grade finish
Weight 12.2 lb. [5.5 kg]
Location Listed for Wet location, tested to IP66 per IEC 60529
Approvals ETL Listed to UL 1598, 2108, 8750 and CSA C22.2# 9 & #250.0
L70 Life > 55,000 hours at 70% lumen maintenance, LM80 / TM-21, see pg 2
Warranty Lifetime Limited Warranty - see warranty for details
IES Files LM-79-08 IES files available
Modifications Any modification or customization is possible - consult factory

LED · INDOOR OUTDOOR · WET LOCATION · IP66 · DIMMABLE · POWERED BY XICATO · TITLE 24 · ETL Intertek

ORDERING LOGIC

Model	-	Driver Location	Dimming	-	Output Direction	Output	CRI	CCT	Reflector	Optical Accessory	-	Shell Color
K4RL	-			-							-	
K4RL		**N**=Integrated **R**=Remote	**N**=None **P**=Phase, 10% **V**=0-10V, 10%		**D** = Down **U** = Up * * includes reflector cover	**07**=700 lm **10**=965 lm **13**=1300 lm **20**=2000 lm **30**=3000 lm* **40**=4000 lm* *available in 83CRI only	**83**=83 **98**=98	**27**=2700K **30**=3000K **35**=3500K **40**=4000K	**08**=08° **13**=13° **20**=20° **40**=40° **60**=60° **83**=83° *2000lm 83CRI or 1300lm 98 CRI max	**NN**=None **DF**=Diffuser Lens **LS**=Spread Lens **WW**=Wall Wash **FT**=Forward Throw **HL**=Hex Louver*		**XX**=v2 color see pg 4 **ZZ**=Custom add **+MF** for Marine Finish

premium drivers (REMOTE location only):
Z1=eldoLED 0-10V, 0%
Z2=eldoLED DALI, 0%
Z3=eldoLED DMX, 0%
Z4=Lutron Hi-Lume™ LDE1, 0-10V, 0%
Z5=Lutron Hi-Lume™ LTEA, Phase, 1%
Z6=Lutron 5-Series™ LDE5, 0-10V, 5%

Example Part Number: **K4RL-NV3-30832720NN-L1**
K AQUA 400 **R**ound **LX** Sconce - **IN**tegrated Driver, 0-10**V** Dim - **D**own, **30**00lm, **83**CRI, **27**00K, **20**°, **NN** No Accessory - **L1** Gloss White

A 1035 22nd Avenue, Unit 1 - Oakland, CA 94606 **P** 510.489.2530 **E** TalkToUs@alwusa.com **W** alwusa.com

WDGE2 LED
Architectural Wall Sconce Precision Refractive Optic

Buy American

Catalog Number

Notes

Type

Hit the Tab key or mouse over the page to see all interactive elements.

Specifications

Depth (D1): 7"
Depth (D2): 1.5"
Height: 9"
Width: 11.5"
Weight: (without options) 13.5 lbs



Introduction

The WDGE LED family is designed to meet specifier's every wall-mounted lighting need in a widely accepted shape that blends with any architecture. The clean rectilinear design comes in four sizes with lumen packages ranging from 1,200 to 25,000 lumens, providing a true site-wide solution. Embedded with nLight® AIR wireless controls, the WDGE family provides additional energy savings and code compliance.

WDGE2 with industry leading precision refractive optics provides great uniform distribution and optical control. When combined with multiple integrated emergency battery backup options, including an 18W cold temperature option, the WDGE2 becomes the ideal wall-mounted lighting solution for pedestrian scale applications in any environment.

WDGE LED Family Overview

Luminaire	Optics	Standard EM, 0°C	Cold EM, -20°C	Sensor	Approximate Lumens (4000K, 80CRI) P0	P1	P2	P3	P4	P5	P6
WDGE1 LED	Visual Comfort	4W		--	750	1,200	2,000	--	--	--	--
WDGE2 LED	Visual Comfort	10W	18W	Standalone / nLight	--	1,200	2,000	3,000	4,500	6,000	--
WDGE2 LED	Precision Refractive	10W	18W	Standalone / nLight	700	1,200	2,000	3,200	4,200	--	--
WDGE2 LED	Precision Refractive	15W	18W	Standalone / nLight	--	7,500	8,500	10,000	12,000	--	--
WDGE4 LED	Precision Refractive			Standalone / nLight	--	12,000	16,000	18,000	20,000	22,000	25,000

Ordering Information

EXAMPLE: WDGE2 LED P3 40K 80CRI VF MVOLT SRM DDBXD

Series	Package	Color Temperature	CRI	Distribution	Voltage	Mounting	
WDGE2 LED	P0[1]	27K 2700K	70CRI[2]	T1S Type I Short	MVOLT	**Shipped included**	**Shipped separately**
	P1[2]	30K 3000K	80CRI	T2M Type II Medium	347[3]	SRM Surface mounting bracket	AWS 3/8inch Architectural wall spacer
	P2[2]	40K 4000K	LW[2] Limited Wavelength	T3M Type III Medium	480[3]	ICW Indirect Canopy/Ceiling Washer bracket (dry/damp locations only)[4]	PBBW 5 surface-mounted back box (top, left, right conduit entry). Use when there is no junction box available.
	P3[2]	50K 5000K		T4M Type IV Medium			
	P4[2]	AMB[2] Amber		TFTM Forward Throw Medium			

Options		Finish
E10WH	Emergency battery backup, Certified in CA Title 20 MAEDBS (10W, 5°C min)	DDBXD Dark bronze
E20WC	Emergency battery backup, Certified in CA Title 20 MAEDBS (18W, -20°C min)	DBLXD Black
PE[3]	Photocell, Button Type	DNAXD Natural aluminum
DMG[4]	0-10V dimming wires pulled outside fixture (for use with an external control, ordered separately)	DWHXD White
BCE	Bottom conduit entry for back box (PBBW). Total of 4 entry points.	DSSXD Sandstone
		DDBTXD Textured dark bronze
		DBLBXD Textured black
		DNATXD Textured natural aluminum
		DWHGXD Textured white
		DSSTXD Textured sandstone

Standalone Sensors/Controls
PIR Bi-level (100/35%) motion sensor for 8-15' mounting heights. Intended for use on switched circuits with external dusk to dawn switching.
PIRH Bi-level (100/35%) motion sensor for 15-30' mounting heights. Intended for use on switched circuits with external dusk to dawn switching.
PIR1FC3V Bi-level (100/35%) motion sensor for 8-15' mounting heights with photocell pre-programmed for dusk to dawn operation.
PIRH1FC3V Bi-level (100/35%) motion sensor for 15-30' mounting heights with photocell pre-programmed for dusk to dawn operation.

Networked Sensors/Controls
NLTAIR2 PIR nLightAIR Wireless enabled bi-level motion/ambient sensor for 8-15' mounting heights.
NLTAIR2 PIRH nLightAIR Wireless enabled bi-level motion/ambient sensor for 15-30' mounting heights.
See page 4 for out of box functionality

Notes
1 Overall height varies based on lumen package; refer to dimensional chart on page 3.
2 Not available with finishes.
3 Not available with emergency options.
4 Must specify voltage 120V or 277V.
5 Available with clear (AR) reflector only.
6 12.5" of plenum depth or top access required for battery pack maintenance.
7 Specify voltage. ER for use with generator supply EM power. Will require an emergency hot feed and normal hot feed.
8 Fixture begins at 80% light level. Must be specified with NPS80EZ or NPS80EZER. Only available with EZ10 and EZ1 drivers.
9 Not available with CP, NPS80EZ, NPS80EZER, NPP16D, NPP-16DER or NBO options.
10 NLTAIR2, NLTAIRER2 and NLTAIREM2 not recommended for metal ceiling installations.
11 Fixture height is 6.5" for all lumen packages with HAO.
12 Must specify voltage for 3000lm and above. 5000lm with marked spacing 24 L x 24 W x 14 H. Not available with emergency battery pack option.
13 Must specify 3150 or 5K driver. Not available with nLight options. Not available with CP. Not recommended for metal ceiling installation. Not for use with emergency backup power systems other than battery packs.

© 2019-2021 Acuity Brands Lighting, Inc. All rights reserved.

Accessories

Ordered and shipped separately.

DLL127F 1.5 JUPhotocell - SSL twist-lock (120-277V) 24
DLL347F 1.5 CUL JU Photocell - SSL twist-lock (347V) 24
DLL480F 1.5 CUL JU Photocell - SSL twist-lock (480V) 24
DSHORT SBK UShorting cap 24
DSX0HS 20C UHouse-side shield for P1,P2,P3 and P4 22
DSX0HS 30C UHouse-side shield for P10,P11,P12 and P13 22
DSX0HS 40C UHouse-side shield for P5,P6 and P7 22
DSX0DDL U Diffused drop lens (polycarbonate) 22
PUMBA DDBXD Square and round pole universal mounting bracket adaptor (specify finish) 25
KMA8 DDBXD U Mast arm mounting bracket adaptor (specify finish) 11
DSX0EGS (FINISH) U External glare shield

For more control options, visit DTL and ROAM online
Link to nLight Air 2




HANDHOLE ORIENTATION
(from top of pole)



Template #8



Tenon Mounting Slipfitter

2-3/8"	RPA	AS3-5 190	AS3-5 280	AS3-5 290	AS3-5 390	AS3-5 320	AS3-5 490
2-7/8"	RPA	AST25-190	AST25-280	AST25-290	AST25-390	AST25-320	AST25-490
4"	RPA	AST35-190	AST35-280	AST35-290	AST35-390	AST35-320	AST35-490

Head Location		Side B	Side B & D	Side B & C	Side B, C & D	Round Pole 28	Side A, B, C & D
Drill Nomenclature	#8	DM19AS	DM28AS	DM29AS	DM39AS	DM32AS	DM49AS
SPA	#8	2-7/8"	2-7/8"	3.5"	3.5"		3.5"
RPA	#8	2-7/8"	2-7/8"	3.5"	3.5"	3"	3.5"
SPUMBA	#5	2-7/8"	3"	4"	4"		4"
RPUMBA	#5	2-7/8"	3.5"	5"	5"	3.5"	5"

DSX0 Area Luminaire - EPA

*Includes luminaire and integral mounting arm. Other tenons, arms, brackets or other accessories are not included in this EPA data.

Mounting Type						
DSX0 LED	0.950	1.900	1.830	2.850	2.850	3.544

© 2011-2021 Acuity Brands Lighting, Inc. All rights reserved.

PHNX DESIGN
1855 EAST SOUTHERN AVE, SUITE 204
MESA, ARIZONA 85204
PHONE: 602.762.7354

©2021 OWNERSHIP OF SERVICE -- All reports, plans, specifications, notes and information prepared by PHNX DESIGN and their consultants shall remain the property thereto. PHNX DESIGN shall retain all common law, statutory and other reserved rights, including the copyright thereto.

12 WEST BREWING COMPANY
LONG BOW DEVELOPMENT
RECKER ROAD AND LONGBOW PARKWAY
MESA, ARIZONA 85215

△	DATE	REVISION
1		
2		
3		
4		
5		

SITE LIGHTING CUT SHEET

A104

PHNX DESIGN #: 21-206